

April 29, 2002

Dave Andresen 20538 97th Ave S Kent, WA 98031

Subject: Review of Deep Well Pumping Test and Well Rating

Dear Mr. Andresen:

We have reviewed the Water Well Report for the Olympic Canal Tracts well and the data collected during the 40-hour pumping test performed by Arcadia Drilling, Inc. Per your request, our primary focus has been to evaluate the pumping test data in an effort to determine an appropriate production rating for the well.

A shut-in pressure reading taken on April 2, 2002 indicated the non-flowing static water level was 5.1 feet above land surface (2.2 psi). Prior to testing on April 5, the well was free flowing at approximately 5.5 gpm. A semi-logarithmic plot of the water level drawdown response in the well is presented in Figure 1. After 10 minutes, the effects of well hydraulics become minimal and the drawdown slope decreases, reflecting aquifer characteristics. This initial slope, seen in Figure 1 between 20 minutes and 190 minutes reflects a near-well aquifer transmiss ivity on the order of 700 gallons/day/foot (gpd/ft). After 190 minutes of pumping, the drawdown curve steepens somewhat, reflecting a negative boundary condition that leads to an implied aquifer transmissivity of roughly 400 gpd/ft. After 600 minutes of pumping, the drawdown slope steepens again, indicating an implied transmissivity on the order of 200 gpd/ft. This slope was maintained throughout the remainder of the test. These are relatively low transmissivity values that indicate poor water transmission capacity in the rock aquifer. Figure 2 is a semi-logarithmic plot of the ratio of t:t' (the ratio of the time since pumping began, t, to the time since pumping ceased, t') versus the recovering water levels; selected actual elapsed recovery times are indicated for reference. The indicated near-well transmissivity from this plot is on the order of 450 gpd/ft.

The primary utility of presenting recovery data in the manner shown in Figure 2 is that it provides a means of evaluating whether the production rate of the pumping test exceeded the volume of natural recharge to the system. When the recovery slope is projected to the left side of the page of this type of plot, it should cross the y-axis at a point roughly coincident with the pre-test static water level. If the projection points to a location substantially above the pre-test static, additional induced recharge to the system is inferred. Similarly, if the projection points below the pre-test static, some overdraught of the system is implied. On Figure 2, the projection of the data from 12 to 72 hours crosses the y-axis at the measurement point at the top of casing.

It should be noted that full recovery to the pre-test condition took more than twice the pumping period (see Figure 2). It is unclear, however, what implications this may have for long-term production from the well. This uncertainty arises because analysis of the test clata was complicated



by the fact that, once the test pump was installed, the well flowed overnight (12+ hours) prior to the initiation of testing. As such, the 40-hour constant-rate test documented herein was initiated at the end of a (12+ hour) constant-head test.

Projecting the late-stage drawdown data from the test suggests that after 100 days of (continuous) production, the pumping water level would drop to approximately 176 feet below the top of casing. In our experience, regularly using appreciably more than 100 feet of drawdown can result in well problems and complicate the long-term maintenance and operation of wells. The test data suggests that your well is capable of producing 16 gpm (continuously) for a period of 100-days with a pumping water level of approximately 100 feet (a design drawdown of 103.5 feet) below top of casing (plus or minus any seasonal variations). The test also demonstrates that the well is capable of short-term, higher production rates of at least 40 gpm, provided the average long-term production does not exceed 16 gpm.

It is not uncommon for wells completed in fractured rock aquifers to have problems with declining water levels and decreasing yield over time. Although Figure 2 does not specifically indicate dewatering is an issue in this setting at this time, the sluggish water level recovery indicates that regular monitoring of water levels should be accomplished. One or two sounding tubes should be installed with the permanent pump to facilitate water level measurement. At a minimum, weekly water-levels should be measured and recorded, preferably when the well has had an opportunity to rest for a minimum of 8 hours. Should the water level be above the top of the casing, a shut-in pressure should be recorded. The second sounding tube could be instrumented with a transducer and datalogger system that would automate this monitoring process, however the collected data would still need to be reviewed regularly. This monitoring equipment would likely cost on the order of \$1,500 to \$1,800 to purchase, dependent upon the length of cable and type/model of unit selected. If so desired, we could assist you in selecting and installing such equipment. The wellhead (including pressure-gauge, sounding tubes, and any installed instrumentation, should be designed to preclude uncontrolled free flow.


We hope that this analysis is of use and would be pleased to provide further assistance, as necessary. Please feel free to contact us with any questions or comments you may have.

Respectfully submitted, Robinson & Noble, Inc.


James E. Hay, L.HG. Senior Hydrogeologist

Cc: Bill Neal, Arcadia Drilling
Jim Parker, Jefferson County PUD

Enclosures







ENCL 16

information submitted to Ecology, it is unclear precisely when these samples were collected. Consequently on 5/22/02 I spoke with Bill Neal of Arcadia Well Drilling. Mr. Neal indicated that they performed a 20 minute drawdown test the morning of 4/4/02. Following this short test, the well recovered slowly. The constant rate test was apparently started at about noon on 4/4/02, and concluded at about 4:30 AM on 4/6/02 (although these times contradict some information submitted). Apparently samples were collected roughly 60 minutes, 12 hours, and 24 hours into pumping, as well as near the conclusion of 40 hours of pumping. The sample taken after 24 hours had a full analysis. The chloride concentrations of the samples collected ranged from 132 to 138 mg/l. The good news is that these levels remained relatively unchanged during the test.

As for your question regarding what type of information would be helpful for Ecology to make a decision, I will make several suggestions. Firstly, I suggest perhaps using Stiff diagrams, etc. in order to analyze inorganic data collected to see if this indicates that the high chloride concentrations observed were the result of hard water (associated with the basalt) or saltwater intrusion. Secondly, it would be helpful to monitor water use and water level (monthly) in the immediate area and to collect water samples for chloride analyses (perhaps quarterly) to measure the response to various pumping rates and seasonal recharge changes.

Additionally, questions remain about the production capacity of the subject well and aquifer. During the aquifer test, the well was still 12.5 feet below full recovery 72 hours after the pump was shut off. Conversely, Mr. Andresen indicated that artesian pressure during prevented them from forcing the drill stem downward. If the subject aquifer were really under artesian pressure, this might indicate an increased ability to keep seawater intrusion at bay. The fact that the well did not recover fully following the pumping test, however, suggests alternate conditions. It has been quite a while since I looked at the data, but it may be prudent to plot the water-level data collected versus the tide changes to see if those had any bearing on the failure of the well to fully recover. I expect however, that you would have noted a cyclical pattern in the water-level or chloride data if the were the case. In short, any refinement of the production capacity of the aquifer would help Ecology when we do make a water right decision.

In summary, the proximity of the subject well to the coast, the high chloride concentrations in the water samples collected, and the failure of the subject well to recover fully, all suggest that this well may be at risk of seawater intrusion. As such, it can be anticipated that increased water production from this well likely would lead to additional seawater intrusion. Nonetheless, it is difficult to predict exactly how the subject aquifer might respond to increasing ground water withdrawals. At a minimum, therefore, if Ecology does ultimately approve this application, it seems

NCL. /c

likely that we would require the system to collect monthly water-use and water-level data, and quarterly chloride data, while this application was in the permit stage, so that we could analyze this prior to that permit going to certificate. Other than that and what I have indicated above, however, I am very open to other suggestions that you might have in order to ascertain the risk of seawater intrusion.

Sincerely,
Tom Culhane
Hydrogeologist
Department of Ecology
Water Resources Program



RCW 90.44.050


Permit to withdraw.

After June 6, 1945, no withdrawal of public ground waters of the state shall be begun, nor shall any well or other works for such withdrawal be constructed, unless an application to appropriate such waters has been made to the department and a permit has been granted by it as herein provided: EXCEPT, HOWEVER, That any withdrawal of public ground waters for stock-watering purposes, or for the watering of a lawn or of a noncommercial garden not exceeding one-half acre in area, or for single or group domestic uses in an amount not exceeding five thousand gallons a day, or for an industrial purpose in an amount not exceeding five thousand gallons a day, is and shall be exempt from the provisions of this section, but, to the extent that it is regularly used beneficially, shall be entitled to a right equal to that established by a permit issued under the provisions of this chapter: PROVIDED, HOWEVER, That the department from time to time may require the person or agency making any such small withdrawal to furnish information as to the means for and the quantity of that withdrawal: PROVIDED, FURTHER, That at the option of the party making withdrawals of ground waters of the state not exceeding five thousand gallons per day, applications under this section or declarations under RCW 90.44.090 may be filed and permits and certificates obtained in the same manner and under the same requirements as is in this chapter provided in the case of withdrawals in excess of five thousand gallons a day.

[1987 c 109 § 108; 1947 c 122 § 1; 1945 c 263 § 5; Rem. Supp. 1947 § 7400-5.]

NOTES:

Purpose -- Short title -- Construction -- Rules -- Severability -- Captions -- 1987 c 109: See notes following RCW 43.21B.001.









INORGANIC CHEMICALS (IOCS) REPORT

	ID No: 11196 M				C CAN			ADDI Source N		1 344
	mple No: 089 54	608	Date Co	llected:	4-6-0	2				
Multipl	e Source Nos: NA			Sam	ple Type: B		Samp	ole Purpos	se: B	
Date Re	eceived: 4-9-02	Dat	e Reported	4-11	-02	Su	pervisor:	GPS		
	JEFFERSON		e Digested:	NA		Group:	(A) B	Othe		^
	Location: NEW	WELL	(4	1:30	em) =	Should	be A.	M.PG	convert	100/
	esults & Bill To: ARC	200				Remark		1 001	10 Thu	wo
			DRILL	1100-			/ \ /	700-	400	aur
	170 SE	WALKE	RPA	RK	RD	-27			- Water	pun
	SHELTW	WA	98	584	+					2
DOH#	ANALYTES	RESULTS	UNITS	SRL	TRIGGER	MCL	EXCI	EEDS	Method/A	nalyst
		FPΔ RF0	GULATED				Trigger?	MCL?		
4	Arsenic	WA	mg/1	0.01	0.05	0.05	mgger:	.WCL.	3113B	T
5	Barium	/ / /	mg/l	0.01	2	2			3113B	1
6	Cadmium		mg/l	0.002	0.005	0.005	-		3113B	+
7	Chromium		mg/l	0.002	0.003	0.003			3113B	1
11	Mercury		mg/l	0.0005	0.002	0.002			3112B	1
12	Selenium		mg/l	0.005	0.05	0.05			3113B	
110	Beryllium		mg/l	0.003	0.004	0.004			3113B	Τ.
111	Nickel		mg/l	0.04	0.1	0.1		4	3111B	
112	Antimony		mg/l	0.005	0.006	0.006			3113B	
113	Thallium		mg/l	0.002	0.002	0.002			3113B	
116	Cyanide		mg/l	0.05	0.2	0.2			4500-CNF	
19	Fluoride		mg/l	0.2	2	4			4110B	
114	Nitrite - N		mg/l	0.5	0.5	1			4110B	
20	Nitrate - N		mg/l	0.5	5	10			4110B	
161	Total Nitrate/Nitrite	V	mg/l	0.5	5	10			4110B	
		EPA REGULA	TED (Second	ary)						1,5
8	Iron	NA	mg/l	0.1	0.3	0.3	<u>-</u>		3111B	
10	Manganese		mg/l	0.01	0.05	0.05			3111B	
13	Silver	V	mg/l	0.01	0.1	0.1			3111B	-
21	Chloride	132	mg/1	20	250	250	NO	NO	4110B	GR
22	Sulfate _	NA	mg/1	10	250	250			4110B	
24	Zinc	4	mg/1	0.2	5	5	-		3111B	-
			EGULATED						1 1 2	
14	Sodium	NA	mg/l	5	A MARK				3111B	1000
15	Hardness	(1/13	mg/l	10			11.2	47.5	2340C	144
16	Conductivity	44.3	umhos/cm	10	700	700	NO	NO		WMI
17	Turbidity	NA	NTU	0.1	11				2130B	-
18	Color		color units	5	15	15	-		2120B	-
26	Total Dissolved Solids	CTATE V	mg/l	150	500	500	-		2540C	-
			REGULATEI							
9	Lead	NA	mg/l	0.002					3113B	
23	Copper	V	mg/l	0.2					3111B	


386 * PROPERTY OF WATER MANAGEMENT LABORATORIES, INC.







System I	DNO: 11196 N	↑ System N	Name: OL	4mp	C CANA	AL T	RACTS	SAI	DDN 1	
	nple No: 0895				4-5-02			Source N	o: NEU)
	Source Nos: NA				ole Type: 3		Samp	le Purpos	se: C	
	ceived: 4-6-02	Date	Reported:		10-02	Su	pervisor:	400		
			Digested:			Group:	(A) B	Othe	or .	1000
	JEFFERSON		Digested:	100	24 hour	roup.	Dumpl	~ Des	Bill Was	1 5/2
Sample	Location: WELL		- Cour	CCE	01 46001			71		
Send Re	sults & Bill To: ARC	ADIA DI	RILLIA	1 G-		Remarks	AA	004	R	
17			OK R							
								34.23		
24	ELTON WA		584				Trivo?		26.1 1/4	
DOH#	ANALYTES	RESULTS	UNITS	SRL	TRIGGER	MCL	EXCÉ		Method/A	Inalyst
		EPA REG	ULATED				Trigger?	MCL?		hal
4	Arsenic	<0.01	mg/l	0.01	0.05	0.05	NO	NO	3113B	MIL
5	Barium	<0.1	mg/l	0.1	2	2			3113B	11/1
6	Cadmium	<0.002	mg/l	0.002	0.005	0.005 -	-	130	3113B	MA
7	Chromium	<0.01	mg/l	0.01	0.1	0.1			3113B	All
11	Mercury	<0.0005	mg/l	0.0005	0.002	0.002			3112B	My
12	Selenium	<0.005	mg/l	0.005	0.05	0.05			3113B	All
110	Beryllium	<0.002	mg/l	0.003	0.004	0.004			3113B	1411
111	Nickel	< 0.04	mg/l	0.04	0.1	0.1			3111B	MIL
112	Antimony	<0-002	mg/l	0.005	0.006	0.006	2 2 2 2	A	3113B	111
113	Thallium	10,001	mg/l	0.002	0.002	0.002			3113B	All
116	Cyanide	< 0.05	mg/l	0.05	0.2	0.2			4500-CNF	100
19	Fluoride	(0,2	mg/l	0.2	2	4			4110B	LHC
114	Nitrite - N	102	mg/l	0.5	0.5	1			4110B	LHL
20	Nitrate - N	(0.2)	mg/l	0.5	5	10			4110B	LHC
161	Total Nitrate/Nitrite	120.4	mg/l	0.5	5	10			4110B	LHC
		EPA REGULAT	ED (Second	ary)						
8	Iron	<0.03	mg/l	0.1	0.3	0.3	NO	NO	3111B	1111
10	Manganese	<0.01	mg/l	0.01	0.05	0.05 =	1	1	3111B	111
13	Silver	< 0.01	mg/l	0.01	0.1	0.1			3111B	401
21	Chloride	< 0.01 137	mg/1	20	250	250			4110B	and
22	Sulfate	45	mg/1	10	250	250			4110B	Suc
24	Zinc	<0.05	mg/1	0.2	5	5			3111B	1401
		STATE RE	GULATED						1 1 1 1 1 1 1 1 1	1.,
14	Sodium	73	mg/l	5		T			3111B	MI
15	Hardness	73	mg/l	10		1			2340C	ow
16	Conductivity	520	umhos/cm	10	700	700	NO	NO	2510B	IHL
17	Turbidity	0.3	NTU	0.1	1		1		2130B	IHL
18	Color	<5	color units	5	15	15	V	NO	2120B	UHC
26	Total Dissolved Solids	NA	mg/l	150	500	500	_	-	2540C -	-
		STATE UNI)						
9	Lead	<0.002	mg/l	0.002		T		1	3113B	M
23	Copper	<0,02	mg/l	0.2					3111B	1
	1 11		0'		9 1 2 3 3 3 3		1	1 10 17 1	1	17111








INORGANIC CHEMICALS (IOCS) REPORT

	ID No: 11961	The same of the sa	Name: OL	Ympi	C CAN	AL T	RACTS	AI	DDNT		
	mple No: 089545				4-4-02				10: NEU		
Multipl	e Source Nos: NA			Sam	ple Type: R		Samı	ple Purpos	se: B		
Date Re	ceived: 4-6-02	Da	te Reported	4-8	ple Type: B	Su	pervisor:	ervisor: WM			
County	JEFFERSON		te Digested:			Group:	\bigcirc B	Oth	er		
	Location: W/F/	LHEAT	TE	ST	2 (1:	2:00	AMA A	ALDNIC	GIHT)		
	esults & Bill To: AR		2011	IAI		Remark	s: A	A AAH	P		
					5	1	1	1001	~ 1		
1/0	SE WALL	KER P	KKD			0	ar count	15 areas	re into p	1 Nes	
OH	ELTON W	A 98	584			1	5/22	lor	20		
DOH#	ANALYTES	RESULTS	UNITS	SRL	TRIGGER	MCL	EXC	EEDS	Method/A	nalyst	
		EPA RE	GULATED				Trigger?	MCL?			
4	Arsenic	NIA	mg/l	0.01	0.05	0.05			3113B	1	
5	Barium		mg/l	0.1	2	2	4. 1		3113B		
6	Cadmium		mg/l	0.002	0.005	0.005			3113B		
7	Chromium		mg/l	0.01	0.1	0.1	100		3113B	32	
11	Mercury		mg/l	0.0005	0.002	0.002			3112B		
12	Selenium		mg/l	0.005	0.05	0.05			3113B		
110	Beryllium		mg/l	0.003	0.004	0.004			3113B		
111	Nickel		mg/l	0.04	0.1	0.1			3111B	4.2	
112	Antimony		mg/l	0.005	0.006	0.006			3113B		
113	Thallium		mg/l	0.002	0.002	0.002			3113B	14.3	
116	Cyanide		mg/l	0.05	0.2	0.2			4500-CNF		
19	Fluoride		mg/l	0.2	2	4		- 19	4110B		
114	Nitrite - N		mg/l	0.5	0.5	1			4110B		
20	Nitrate - N		mg/l	0.5	5	10		21.14.3	4110B		
161	Total Nitrate/Nitrite	V	mg/l	0.5	5	10			4110B		
		EPA REGULA	TED (Second	ary)						1 5	
8	Iron	NA	mg/l	0.1	0.3	0.3	-		3111B		
10	Manganese		mg/l	0.01	0.05	0.05			3111B		
13	Silver	4	mg/l	0.01	0.1	0.1			3111B		
21	Chloride	138	mg/1	20	250	250	NO	NO	4110B	Die	
22	Sulfate -	NIA	mg/1	10	250	250			4110B		
24	Zinc	1	mg/1	0.2	5	5			3111B		
		STATE R	EGULATED								
14	Sodium	NA	mg/l	5					3111B	T. Carrie	
15	Hardness	1	mg/l	10			75.		2340C		
16	Conductivity	535	umhos/cm	10	700	700	NO	NU	2510B	LHE	
17	Turbidity	NA	NTU	0.1	1				2130B		
18	Color		color units	5	15	15			2120B		
26	Total Dissolved Solids		mg/l	150	500	500			2540C		
***		STATE UN	REGULATEI)			1.5		-11		
9	Lead	NA	mg/l	0.002				113	3113B	1 1 9 9	
23	Copper	1	mg/l	0.2	F. N			1.00	3111B		
COMM								1 1 1	120	-	

**





1515 80th St. E. Tacoma, WA 9 (253) 531-3121



INORGANIC CHEMICALS (IOCS) REPORT

System ID No: 11 System Name: OLYMPIC CANAL TRACTS ADDNI Date Collected: 4 -4-02 DOH Source No: NEW) Lab/Sample No: 08954578 Sample Type: 3 Sample Purpose: B Multiple Source Nos: 4-8-02 Date Reported: Supervisor: WMA Date Received: 4 Date Digested: N/A Group: About (1:00 PM) PT per conversed Sample Location: WELLHEAD TEST 1 Send Results & Bill To: Remarks: ARCADIA DRILLING WALKER PIC 98584 **EXCEEDS** Method/Analyst **RESULTS UNITS** TRIGGER MCL DOH# **ANALYTES** SRL **EPA REGULATED** Trigger? MCL? 0.01 0.05 4 Arsenic mg/l 0.05 3113B 2 2 5 Barium 0.1 3113B mg/10.002 0.005 0.005 6 Cadmium mg/I3113B 7 Chromium 0.01 0.1 0.1 3113B mg/l11 Mercury mg/I 0.0005 0.002 0.002 3112B Selenium 0.005 0.05 0.05 3113B 12 mg/1110 Beryllium 0.003 0.004 0.004 3113B mg/1Nickel 0.04 0.1 0.1 3111B 111 mg/lAntimony 0.005 0.006 0.006 3113B 112 mg/1 Thallium 0.002 0.002 0.002 3113B 113 mg/1Cyanide 0.05 0.2 0.2 4500-CNF 116 mg/l Fluoride 19 mg/l 0.2 2 4 4110B 114 Nitrite - N 0.5 0.5 1 4110B mg/l 20 Nitrate - N mg/l 0.5 5 10 4110B Total Nitrate/Nitrite 0.5 5 10 4110B 161 mg/l EPA REGULATED (Secondary) NIA 0.1 0.3 0.3 3111B 8 Iron mg/lManganese 0.01 0.05 0.05 3111B 10 mg/1 Silver 0.01 0.1 0.1 3111B 13 mg/1 Chloride NO 136 21 20 250 250 4110B SW mg/122 Sulfate 10 250 250 mg/14110B 24 Zinc 0.2 5 5 mg/13111B STATE REGULATED Sodium 14 mg/15 3111B 15 Hardness 10 mg/12340C NO 1.41 NO 16 Conductivity 53 umhos/cm 10 700 700 2510B 17 Turbidity NTU 0.1 1 2130B 18 Color color units 5 15 15 2120B 26 Total Dissolved Solids mg/l 150 500 500 2540C STATE UNREGULATED 9 Lead mg/l 0.002 3113B 23 Copper 0.2 mg/13111B **COMMENTS:** AND CONDUCTIVITY ONLY CHLORIDE





VOLATILE ORGANIC CHEMICALS (VOC's) ANALYSIS REPORT EPA TEST METHOD - 524.2

System Name: Olympic Canal Tracts Addition 1 system ID No.: 11196M DOH Source No.: New .ab/Sample No.: 08977959 Date Collected: 04/05/02 Sample Purpose : C Multiple Source Nos.: N/A Sample Type: B Supervisor: UMA Date Received: 04/06/02 Date Reported: 05/15/02 Date Analyzed: 04/15/02 Analyst : LHL County : Jefferson Group : A Sample Location: Well Head Send To: Arcadia Well Drilling Bill To : SAME 170 SE Walker Park Rd.; Shelton, WA 98684

Note: Failed Resampling After 30 Days Grace Period

DOH#	ANALYTES	RESULTS	UNITS	SRL	TRIGGER	MCL	EXCEE	S
4.200	ne la compania de la	THE CONTRACTOR OF THE SECOND					Trigger?	MCLT
45	Vinyl Chloride	ND	ug/L	0.5	0.6	2	NO	NO
46	1,1 - Dichloroethylene	ND	ug/L	0.5	0.5	7	NO	NO
47	1,1,1 - Trichloroethane	ND	ug/L	0.5	0.5	200	NO	NO
48	Carbon Tetrachloride	ND	ug/L	0.5	0.5	6	NO	NO
49	Benzene	ND	ug/L	0.5	0.5	Б	NO	NO
50	1,2 - Dichloroethene	ND	ug/L	0.5	0.5	5	NO	NO
51	Trichloroethylane	ND	ug/L	0.5	0.5	5	NO	NO
52	1,4 - Dichlorobenzene	ND	ug/L	0.5	0.5	75	NO	NO
56	Dichloromethane	ND	ug/L	0,5	0.5	5	NO	NO
57	trans-1,2 - Dichloroethylene	ND	ug/L	0.5	0.5	100	NO	NO
60	cis-1,2 - Dichloroethylene	NO	ug/L	0.5	0.5	70	NO	NO
63	1,2 - Dichloropropana	ND	ug/L	0.5	0.5	5	NO	NO
66	Toluene	0.7	ug/L	0.5	0.5	1000	Yes	NO
67	1,1,2 - Trichloroethane	ND	ug/L	0.5	0.5	5	NO	NO
68	Tetrachioroethylena	· ND	ug/L	0.5	0.6	5	NO	NO
71	Chlorobenzene	ND	ug/L	0.5	0.5	100	NO	NO
73	Ethylbenzene	ND	ug/L	0.5	0.5	700	NO	NO
76	Styrene	1.4	ug/L	0.5	0.5	100	Yes	NO
84	1,2 - Dichlorobenzane	ND	ug/L	0.5	0.5	600	NO	NO
95	1,2,4 - Trichlorobenzene	ND	ug/L	0.5	0.5	70	NO	NO
160	Total Xylenes	ND	ug/L	0.5	0.5	10000	NO	NO
74	m/p Xylenes (MCL for Total)	ND	ug/L	0.5	0.5		NO	
75	a - Xylene (MCL for Total)	ND	ug/L	0.5	0.5		NO	100
		AND SELVEN THE CONTRACT OF THE SERVEN						100
27	Chloroform	ND	ug/L	0.5	0.5		NO	
28	Bromodichloromethana	ND	ug/L	0.5	0.5		NO	
29	Chlorodibromomethane	ND	ug/L	0.5	0,5		NO	
30	Bromoform	ND ·	ug/L	0.5	0.5	Enternon	NO	
53	Chloromethane	ND	ug/L	0.5	0.5		NO	
54	Bromomethane	ND	ug/L	0.5	0.5		NO	
55	Chloroethane	ND	ug/L	0.5	0.5		NO	

ENCL 18cz

e No.: 08977959

VOC ANALYSIS REPORT - METHOD 524.2

Water Management Laboratories, Inc. 1515 80th St. E. Tacoma, WA 98404 (253) 531-3121

DOH #	ANALYTES	RESULTS	UNITS	SRL	TRIGGER	MCL	EXC	EEDS
nd verione		HZAMONO PROPRATE A CONTROL (CONTROL CONTROL CONTROL CONTROL CONTROL CONTROL CONTROL CONTROL CONTROL CONTROL CO					Trigger?	MCL?
58	1,1 - Dichlorosthane	ND	ug/L	0.5	0.5		NO	
59	2,2 - Dighioropropane	ND	ug/L	0.5	0.5		NO	
62	1,1 - Dichloropropene	ND	ug/L	0.5	0.5		NO	
64	Dibromomethane	ND	ug/L	0.5	0.5		NO	
70	1,3 - Dichloropropane	ND	ug/L	0.5	0.5		NO	
72	1,1,1,2 - Tetrachiroroethane	ND	ug/L	0.5	0.5		NO	
78	Bromobenzene	ND	ug/L	0.5	0.5		NO	
79	1,2,3 - Trichloropropane	ND	ug/L	0.5	0.5		NO	
80	11,1,2,2 - Tetrachloroethane	ND	ug/L	0.5	0.5		NO	
81	o'- Chlorotoluene	· ND	ug/L	0.5	0.5		· NO	
82	p - Chlorotoluene	ND	ug/L	0.5	0.5		NO	92.3
83	m - Dichlorobenzene	ND	ug/L	0.5	0.5		NO	- 64
154	1,3 - Dichloropropens	ND	ug/L	0.5	0.5		NO	100
		Baran Banagerayan		S. 287-1979				1
65	cis-1,3 - Dichloropropene	ND	ug/L	0.5	0.5	<u>"</u>	NO	113/4
69	trans-1,3 - Dichloropropene	ND	ug/L	0.5	0.5		NO	
85	Fluorotrichloromethane	ND ·	ug/L	0.5	0.5	21.27.5	NO	
86	Bromochloromethane	ND	ug/L	0.5	0.5	-12-14	NO	
87	Isopropylbenzene	ND	ug/L	0.5	0.5		NO	12.00
88	n - Propylbenzene	ND	ug/L	0.5	0.5		NO	
89	1,3,5 - Trimethylbenzene	ND	ug/L	0.5	0.5	M. Property Co.	NO	
90	t - Butylbenzene	ND	ug/L	0.5	0.5		NO	
91	1,2,4 - Trimethylbenzene	ND	ug/L	0.5	0.5		NO	
92	s - Butylbenzene	ND	ug/L	0.5	0.5		NO	12.7
93	p - Isopropyltoluene	ND	ug/L	0.5	0.5		NO	
94	n - Butylbenzene	ND	ug/L	0.5	0.5		NO	
96	Napthalene	ND	ug/L	0.5	0.5		NO	
97	Hexachiorobutadiene	ND	ug/L	0.5	0.5		NO	
98	1,2,3 - Trichlorobenzene	ND	ug/L	0.5	0.5		NO	
102	EDB (Confirm by 504.1)	ND	ug/L	0.5	0.5		. NO	3 1
103	DBCP (Confirm by 504.1)	ND	ug/L	0.5	0.5		NO	
162	Dichlorodifluoromethane	ND	ug/L	0.5	0.5	15 1 1 1 2 2	NO	
N/A	Nitrobenzene	ND	ug/L				The second second	
N/A	MTBE	ND	ug/L	0.5	0.5		NO	1

VOTES:

iRL (State Reporting Level): Indicates the minimum reporting level required by the Washington Department of Health (DOH).

rigger Level: DOH Drinking Water response level. Systems with compounds detected at concentrations in excess of this level are required to take additional samples. Contact your regional DOH office for further information.

ACL (Maximum Contaminant Level): If the contaminant amount exceeds the MCL, Immediately contact your regional DOH office.

IA (Not Analyzed): In the RESULTS column indicates this compound was not included in the current enalysis.

(Not Detected): In the RESULTS column indicates this compound was analyzed and not detected at a level greater than or equal to the SRL.

< : indicates less than.

Comments: A maximum contaminant level of 80 ug/L total Trihalomethanes (Compounds 27-30) is allowed.

Method 524: VOC's

ENCL 182

Weington State Public Health Laborate 610 NE 150th Street, Shoreline WA. 98155-1 Phone (206) 361-2896 FAX (206) 361-2899

RADIONUCLIDE ANALYSES REPORT

System ID No.: 11196M	System Na	me: Olympi	c Canal Tracts Ad. 1			
Lab/Sample No: 02369209		Date Collec	ted: 4/5/02 13:00		DOH Source No: New Source	
Multiple Source Nos:			Sample Type: B		Sample Purpose: C	
Date Received: 4/9/02 Date Reporte		Reported:	05/08/02	108/02 Supervisor: 98 prs		
Date Analyzed:			1/11/02 Analyst:		:: SLB	
County: Jefferson		Group: A				
Sample Location: Well head			the second			
Send Report To: Arcadia Drilling In	0.		Bill To: Arcadia Drilling Inc.			
170 SE Walker Park Rd.			170 SE Walker Park Rd.			
Shelton, WA 98584			Shelton, WA 98584			

DOH #	ANALYTES	LAB MDA	RESULTS	UNITS pCi/	DATE ANALYZED	MCL	ANALYST/METHOD
			an and the same of the same of	447 Juni 17			
39	Radium 226			pCi/l		3	
40	Radium 226 + 228			pCi/l		5	
41	Gross Alpha	3	ND	pCi/l	4/11/02	15*	SLB/EPA 900.0
42	Gross Beta	7	ND	pCi/l	4/11/02	50	SLB/EPA 900.0
43	Tritium			pCi/l		20000	
44	Strontium 90			pCi/I	Care S	8	
107	Cestum 134			pCi/l		本本	
108	Iodine 131			pCi/l	Shart	**	
				(4) - Tucke.			
105	Uranium			pCi/l			
109	Radon			pCi/l		1	

NOTES:
MCL: Maximum Contaminant Level. If the contaminant amount exceeds the MCL, immediately contact your regional DOH office. MDA: Minimum Detectable Amount.

NA (Not Analyzed) indicates this analyte was not included in the current analysis.

ND (Not Detected) indicates this analyte was analyzed and not detected at a level greater than or equal to the MDA.

* Excluding Uranium

** The MCL for beta particle and photon radioactivity from man-made radionuclides is the average annual concentration which shall not produce an annual dose equivalent to the total body or any internal organ greater than four milli-rem/yr.

Comments his sample is for a new well—Well is not on line.		
door addoor on any the state of		and the second
	The second second second	Control of the Contro

Charge Amount: \$73.00



MANAGEMENT LABORATORIES INC.

Kinko's 24Hr Fax Service 1515 80th St. E. Tacoma, WA 98404 (253) 531-3121

SEE BACK FOR INSTRUCTIONS

SE HEAVY PEN ONOTWRITE IN SHADED AREAS

,2,3 ENCL 18e, INORGANIC CHEMICALS (IOCS) REPORT

	Source Nos: NA			Sam	ple Type: B		Samp	le Purpos	ie: B	
te Re	ceived: 4-6-02	Dat	e Reported:		7-02	Su	The state of the s	WMA		
unty:	JEFFERSON		e Digested:	A		Group:	(A) B	Othe		
								Ome	=	
	Location: WELL	HEAD_	TES		(1:0	O PW	2)			
nd Re	sults & Bill To: AR	ADIA	DRIL	LINI		Remark	S AAO	MUR		
						1		UIL	1	
	SE WAL			02		-			· · · ·	
)HE	LTON WA	98	584	-						
HH(ANALYTES	RESULTS	UNITS	SRL	TRIGGER	MCL	EXCE	EDS	Method / A	nalyst
		EPA REC	GULATED				Trigger?	MCL?		
4	Arsenic	NIA	mg/l	0.01	0.05	0.05			3113B	T
5	Barium	4	mg/l	0.1	2	2			3113B	1
6	Cadmium		mg/l	0.002	0.005	0.005			3113B	
7	Chromium		mg/l	0.01	0.1	0.1		4 - 1	3113B	
1	Mercury		mg/l	0.0005	0.002	0.002			3112B	100
2	Selenium		mg/l	0.005	0.05	0.05			31138	
10	Beryllium		mg/1	0.003	0.004	0.004			3113B	1114
11	Nickel		mg/l	0.04	0.1	0.1			3111B	
12	Antimony	4.5	mg/l	0.005	0.006	0.006			3113B	
13	Thallium		mg/l	0.002	0.002	0.002		and the second	31138	
16	Cyanide		mg/l	0.05	0.2	0.2	Action Co.		4500-CNF	
9	Fluoride		mg/1	0.2	2	4			41108	
14	Nitrite - N		mg/l	0.5	0.5	1		in the second	4110B	
20	Nitrate - N	1	mg/l	0.5	5	10		erier C	41108	100000
61	Total Nitrate/Nitrite		mg/l	0.5	5	10			4110B	
		EPA REGULA	TED (Second	ary)			and the second	100	1	4344
8	Iron	NIA	mg/l	0.1	0.3	0.3	And the second		31118	-
10	Manganese		mg/l	0.01	0.05	0.05			3111B	
3	Silver	V	mg/l	0.01	0.1	0.1	,000 Line	12 Table 1 1	3111B	78.3
27	Chloride	134	mg/1	20	250	250	MO	NO	4110B	0~3
12	Sulfate	NA	mg/1	10	250	250			4110B	
14	Zinc	1	mg/1	0.2	5	5	1132 15 15		31118	
		STATE R	GULATED							
.4	Sodium	NIA	mg/l	5			FA 545 54 54	1 4 9 7	31118	
5	Hardness	-	mg/l	10			500		2340C	
.6	Conductivity	537	umhos/cm		700	700	NO	MO	25108	LHC
7	Turbidity	NIA	NTU	0.1	1				21308	1.38
8	Color	-	color units	5	15	15			2120B	
6	Total Dissolved Solids	L W	mg/l	150	500	500			2540C	
		STATE UN	REGULATE)				anger an		
7	Lead	NIA	mg/l	0.002					31138	
3	Copper	1 1	mg/I	0.2					31118	1
MM	The state				DUCTIVIT	()	11_			

. MOY-01-2002 FRI 04:20 PM ARCADIA DRILLING INC	FAX NO. 360 426 1455		P. 15
WATER WEL REPORT	CURRENT W157941		1, 15
Profile Original & 1st copy - Beology, 2ad copy - owner, 3rd copy - driller	Unique Ecology Well ID Tag No^	G F 3 6'8	
Construction/Decommission ("x" in circle)			-
O Construction O Decomplission ORIGINAL CONSTRUCTION Notice	Water Right Permit No. G2-2960		104
of Intent Number	Property Owner NameOlympic Car	ial Tra	cts
PROPOSED USE: Domestic Industrial Municipal DeWater Dirigation Test Well Dother	Well Street Address 310713 Hwy		
TYPE OF WORK: Owner's number of well (if more than one)	City Brinnen County:		THE RESERVE TO SHARE THE PARTY NAMED IN
New Well Reconditioned Method: Dug Bored Driven Cable Rotary Jetted	Location NW 1/4- U/4 SE 1/4 Sec 21		- 4
DIMENSIONS: Diameter of well inches, drilled ft.	Lat/Long: Lat Deg	Lar Min/Sc	C
Depth of completed wellft.	REQUIRED) Long Deg	Long Min!	Sec
CONSTRUCTION DETAILS	Tax Parcel No 502214003		
Casing Weided Diam from ft. w Installed: Liner installed Diam from ft. w Installed: Liner installed Diam from ft. w Installed: Diam ft.	CONSTRUCTION OR DECOMMISSI Formation: Describe by color, character, size of m kind and name of the material in each stratum per entry for each change of information, indicate all v (USS ADDITIONAL SHEETS IF NECESSARY.)	sherial and street and street with water encount	ructure, and the
Type of perforator used	MATERIAL	FROM	TO
SIZE of perfs in by in and no. of perfs from ft. to ft.	Black basait	357	398
Screens: Yes No K-Pac Location	Purple fractured besalt		409
Manufacturer's Name TypeModel No	Gray, graen basait with		
Diam Slot Size from ft. to ft.	white quartz		421
Diam. Slot Size from ft. to ft.	Black basait	421	438
Gravel/Filter packed: Yes No Size of gravel/sand	Purple basalt	438	444
Materials placed from ft. to ft.	Fractured gray and	444	1.1(12)
Surface Seals Yes No To what depth?ft	green basalt		445
Materials used in seal	Gray & graen basait	445	452
Did any stress contain unusable weter? Type of water? Depth of strate.	Fractured gray & green	452	
Method of scaling strata off	basalt w/white quartz-w	Name of Street, or other Designation of the Owner, where the Parket of the Owner, where the Owner, which the Owner, where the Owner, where the Owner, which the	456
PUMP: Manufacturer's Name	Black baselt Fractured black baselt	456	465
Гурас Н.Р.	Gray & green basait	465	479
WATER LEVELS: Land-surface elevation above mean sea levelfi_	Grayish brown basait	479	480
Static levelft. below top of well	Gray basait	480	485
Artesian water is controlled by	practured black, green	485	
(cap, yalve, etc.)	basalt with quartz		489
WELL TESTS: Drawdown is amount water level is lowered below static level.	Black baselt	489	502
Vas a pump isst made? Tyes Tho if yes, by whom? Teld:hrshrs.	Fractured black, green	502	
field: gal/min with th drawdows after hrs.	basalt with quertz, wate	r	509
(leid: gal/min, with ft drawdown after hrs. ecovery data (time taken as zero when pump turned 95%water level measured from	Black basait, water	509	512
ell top to water level)	Fractured black pasait	512	
ime Water Level Time Water Level Time Water Level	water		515
	Black basalt, water	515	532
ate of tost	Fractured black basalt	532	
aller test gal/min. with ft. drawdown after bis.	water		534
irtest gal/min. with stem set at ft. for hrs.	CONTINUED ON NEXT PAGE		
rtesian flow	Start Date 4-1-02 Completed Date	4-2-0	02
ELL CONSTRUCTION CERTIFICATION: I constructed and/or accept responds the information representation and the information representation representation and the information representation representation and the information representation representat	asibility for construction of this well, and its constructed above are true to my best knowledge and	mpliance wi	th all
Driller Engineer Traines Name (Print) Rogerav Phythlan			Inc.
riller/Engineer/Traince Signature	- Address 170 BE Walker Par	k Roa	d
riller or Traince License No. 2053	City, State, Zip Shelton WA	98584	dia to
f traince, licensed driller's	Registration NoDate	4-1	2-02-
-Described in order 4-to-Aven & Ma.	France is an Fant Caparamity Employer. E	CY 050-1-20	(Rev 401)

Ecology is an Equal Opportunity Employer. ECY 050-1-20 (Rev 401)

NOV-U1-2002 FRI 04:19 PM ARCADIA DRILLING INC	FAX NO. 360 426 1455		P. 14
WATER WELL REPORT	CURRENT 5		
[[W]] [V.] Original & Ist copy - Ecology, 2nd copy - nwner, 3rd copy - driller	Notice of Intent N W137941	7.60.	
Construction/Decommission ("x" in circle)	Unique Ecology Well ID Tag No. A G P	308	
⊗ Construction	Water Right Permit No. G2-296	05	
O Decommission ORIGINAL CONSTRUCTION Notice of Intent Number	- Olympia Ca	nal Ta	
PROPOSED USE: Domestic Ladustrial Municipal	Property Owner Name Olympic Ca		
DeWater Linigation Test Well Other	Well Street Address 310713 Hwy		
YPE OF WORK: Owner's number of well (if more than one)	City Brinnon County:		
New Well Reconditioned Method: Dug Bored Driven	Location NW 1/4 1/4 SE 1/4 Sec 21	25 N R	S M HWW
Despened Cable X Rotary Detect	Lat/Long: Lat Deg	Tat Min / Can	WWW
DIMENSIONS: Diameter of well 6 inches, drilled 562 ft.	(s,t,r still)		-
Depth of completed well 562 ft.	REQUIRED) Long Deg Tax Parcel No. 5.0 2 2 1 4 0 0 3	Long Min/Se	×
CONSTRUCTION DETAILS			
Tasing Medded 6 Diam from +2 ft to 102 ft anstalled: Thing installed 4.5" Diam from 4 ft to 562 ft	CONSTRUCTION OR DECOMMISSION Formation: Describe by color, character, size of many		
Threaded Diam from ft to ft	kind and name of the material in each stratum per entry for each change of information. Indicate all v	otrated, with a	t least one
erforations: A Yes A No	(USE ADDITIONAL SHEETS IF NECESSARY.)) Asiat circonsfe	red.
ype of perforator used Dr III	MATERIAL	FROM	TO
IZE of perfs 1 in by 1 in and no. of perfs 320 from 402 ft. to 562 ft.	Redish brown silty clay	. 0	7
ersent: Yes No K-Pas Location	Gray slit binding fine	7	
ype Model No.	to medium black sand		
iam Slot Size from ft to ft.	and grave! Brown fine to medium		11
sm. Stor Size from the to the		11	
raye/Filter packed: Yes No Size of grave/sand	sand and grave! Moist brown fine to	4.4	14
Saterials placed from ft. to ft.	medium sand some gravel	14	2.5
Tamrials used in seal Bentonite	Brown silt to fine sand	26	31
Pid any atrata contain unutable water? □Yes ☒ No	Gray silt to fine sand	31	50
yps of water? Depth of strata	Black fractured basait	50	
UMF: Manufagamer's Name	moist, silt to fine		
уре:	black sand Black fractured basait		78
ATER LEVELS: Land-surface elevation above mean sea level 10 ft.	with silty gray clay	7 8	96
ratic level Flowing ft, below top of well Date 4-2-02 tasian pressure 22 lbs. per square inch Date 4-2-02	Brown weathered basait	96	105
designed by many of the same o	Gray sandstone	105	126
(esp.valve, etc.)	Black basalt	126	173
ELL TESTS: Drawdown is amount water level is lowered below static level.	Blue bassit	173	182
alde dal ferrire table & densariasses after large	Fractured blue basalt	182	184
eld: gal /min. with ft drawdown after hrs.	Black besalt	184	253
ield: gal/min. withft. drawdown afterbra.	Blue basait	253	258
annum, Anin film a saless on wood titles more stricted as foreign that I made und form	Black fractured basalt	258	262
top to water level) SEE ATTACHED REPORT		262	284
tovery data (time taken as zero when pump turned off) water level measured from the property of the property o	Black dense bassit	. 284	
covery data (time taken as zero when pump turned off) (water level measured from ill top to water level) SEE ATTACHED REPORT THE Water Level Time Water Level Time Water Level	Fractured black basalt	284	286
Covery data (time taken as zero when pump turned off) (water level measured from it top to water level) SEE ATTACHED REPORT THE Water Level Time Water Level Time Water Level Le of test	Fractured black basait Black basait	286	340
covery data (time taken as zero when pump turned off) water level measured from it top to water level SEE ATTACHED REPORT Water Level Time Water Level Time Water Level Wa	Fractured black basait Black basait Purple basait	77	
ate of test gal/min. with ft. drawdown after hrs. liter test gal/min. with stem set at 5 6 G ft. for 1 hrs. liter flow 3 gal/min. with stem set at 5 6 G ft. for 1 hrs. liter flow 3 gal/min. with 2 gal/min. with stem set at 5 6 G ft. for 1 hrs.	Fractured black basait Black basait	286	3 4 0 3 5 7

Mastington Aert construction standards: Materials race and the implimental tebor	
Driller Engineer Trainer Name (Print) Rosersy Phythlan	Drilling Company Arcadia Orilina ina
M Driller - Hugineer - Trainer Name (Print) Rosersy Phythlen Driller/Engineer/Trainee Signature	Address 170 SE Walker Park Road
Oriller or Trainee License No. 2053	City, State, Zip Sheiton WA 98584 Contractor's ARCADD 098K1
If trainee, licensed driller'sSignature and License no	Contractor's ARCADD 098 K1 Registration No. Date CONTRACTOR Date Date

Temperature of water_

NOV-01-2002 FRI 04:20 PM ARCADIA DRILLING INC	FAX NO. 360 426 1455	P. 16
WATER WEI PREPORT	Page 3 of 3 CURRENT Notice of Intent	11 10
Provided Original & Ist copy - Ecology, 2nd copy - owner, 3rd copy - driller	Unique Ecology Well ID Tag No. A G	P368
Construction/Decommission ("z" in circle)		
O Construction	Water Right Permit No. G2-2950	5
O Decommission ORIGINAL CONSTRUCTION Notice of Intent Number	- Alumnia Can	al Tunata
PROPOSED USE: Domestic industrial Municipal	Property Owner Name Olympic Can	
DeWater Irrigation Test Well Other	Well Street Address 310713 Hwy 1	
TYPE OF WORK: Owner's number of well (if more than one)	City Brinnen County:	Jafferson
New Well Reconditioned Method: Dug Bored Driven	Location NW 1/4-1/4 SE 1/4 Sec 21 Tw	25N R 2W EWM ch
Despend Cable Rotary Jetted		
DIMENSIONS: Diameter of well inches, drilled ft.	Lar/Long: Lar Deg L	at Min/Sec
Depth of completed well ft.	REQUIRED) Long Deg.	ong Min/Sec
CONSTRUCTION DETAILS	Tax Parcel No. 50.2214003	
Casing TWolded * Diam from ft to	CONSTRUCTION OR DECOMMISSION	PROCEDURE
Installed: Liner installed Diam. from ft. to	Formation: Describe by color, character, size of mate	erial and structure, and the
Threaded Diam. fromft tof	kind and nature of the material in each stramm pence	rated, with at least one
Perforations: Yes No	catty for each change of information, indicate all was (USE ADDITIONAL SHEETS IF NECESSARY.)	er encountered.
Type of perforator used		FROM TO
SIZE of perfsin_byin_and no. of perfsfromft. toft	Green & Black basalt	534
Screens: Yes No K-Pac Location	water	
Manufacturer's Name	Fractured black basait	547
Type Model No.	water	549
Diam Slot Size from A to A.	Dense bilack basait,	549
	water	5'5 9
Gravel/Filter packed: Yes No Size of gravel/sand Materials placed from ft to ft	Black fractured basalt	250
Surface Seal: Yes No To what depth? ft	with some rounded	559
Materials used in scal	pes-gravel & water	562
Did any strate contain unusable water? Yes No	Pag diatel a well	742
Type of water? Depth of strau.		
Mathod of sealing strata off		
PUMP: Manufacturer's Name		
Туро: Н.Р.		
WATER LEVELS: Land-surface elevation above mean sea levelft.		
Static level		
Artesian want is controlled by		
(cap,yalvc, etc.)		
WELL TESTS: Drawdown is amount water level is lowered below static level.		
Was a pump test made? [Yes] No If yes, by whom?		
Yield: gal/min. with ft drawdown after hrs. Yield: gal/min. with ft drawdown after hrs.		
rield: gal/min. with nt drawdown after hrs.		
scovery data (time taken as zero when pump turned off)(water level measured from		
vali top to water level) Sime Water Level Time Water Level Time Water Level		
THE PARTY AND THE PARTY		
The same of the sa		
Page of test		
Saffer test gal/min. with ft. drawdown after hrs.		
Airest gal/min, with stem set at ft. for bre.		
Artesian flow	Start Date4-1-02Completed Date_	4-2-02

WELL CONSTRUCTION CERTIFICATION: I constructed and/or accept responsibility for construction of this well, and its compliance with all

Was a chemical analysis made? Yes No

Washington well construction standards. Materials used and the information repo	ned above are true to my best knowledge and belief.
Driller Hingineer Traince Name (Print) Rogeray Phythian	Drilling Company Arcadia Drilling inc
	Address 170 SE Walker Park Road
Driller or Traince License No. 2053	City, State, Zip Sheiton WA 98584
If trainee, licensed driller's Signature and License no.	Contractor's ARCADDIO98K1 Registration No. Date 4-15-0? Ecology is an Pougl Concentrative Employer. ECY 050-1-20 (Rev 4/01)



IKL 142



Customeri Canal View Tracts 310713 Hwv 101

Brinnon, WA 98302 Contact: Dave Andreson/ Dick Wasson

Phone: (253) 852-3687 Dave Phone: (208) 242-2072 Dick Fax:

E-mall Cells

Project: Deep Well Drill and Test

Date of Test: 4/5 - 4/8 2002

ump Test D			ssurements are f			Recovery D	
TIME	GPM	feel-10ths LEVEL	TIME	gallons per min. GPM	LEVEL	TIME	tact-10ths
10 Sec.	40 .	3.3	7 Hr.	40	125.7	10 Sec.	149.
20 Sec.	40	6.0	8 Hr.	40	127.5	20 Sec.	7.181
30 Sec.	40	9,3	9 Hr.	40	128,5	30 Sec.	137.
40 Sec.	40	16.0	10 Hr.	40	129.6	40 Seo.	1011
50 Sec.	40	20.0	11 Hr.	40	131.0	50 Sec.	125,
60 Sec.	40	24.2	12 Hr.	40	132.2	60 Sec.	121.
70 Sec.	40	28.6	13 Hr.	40	133.5	2 Min.	113
80 Sec.	40	31.9	14 Hr.	40	135.6	3 Min.	105
90 Sec.	40	35,0	15 Hr.	40	135.4	4 Min.	99
100 Sec.	40	36.0	16 Hr.	40	137.6	5 Min-	92
110 Sec.	40	40.8	17 Hr.	40	138.5	8 Min.	88
2 Min.	40	42.9	18 Hr.	40	139.6	7 Min.	83
2.5 Min.	40	50.9	19 Hr.	40	140.3	8 Min.	81
a Min.	40	56.3	20 Hr.	40	140.9	9 Min.	79
3.5 Min.	40	61,5	21 Hr.	40	141.9	10 Min.	77
4 Min.	40	65.7	22 Hr.	40	143.0	11 Min.	76
4.5 Min.	40	69.7	28 Hr.	40	143.9	12 Min.	76
5 Min.	40	72.9	24 Hr.	40	144.9	19 Min.	74
6 Min.	40	78.5	25 Hr.	40	147.8	14 Min.	73
7 Min.	40	82,5	26 Hr.	40	149.9	15 Mln.	72
e Min.	40	86.2	27 Hr.	40	151.9	20 Min.	70
9 Min.	40	89.0	29 Hr.	40	152,6	25 Mln.	69
TO Min.	40	91.2	29 Hr.	40	153.4	30 Min.	67
11 Min.	40	93.3	30 Hr.	40	154.2	1 Hr.	62
12 Min.	40	94.8	31 Hr.	40	155.4	2 Hr.	50
13 Mln.	40	95.7	32 Hr.	40	158.0	3 Hr.	58
14 Min.	40	97.1	33 Hr.	40	156.5	4 Hr.	51
15 Mln.	40	98.1	34 Hr.	40	157.0	6 Hr.	45
20 Mln.	40	101.1	35 Hr.	40	157.6	6 Hr.	4
25 Min.	40	102.9	36 Hr.	40	158.0	7 Hr.	41
30 Min.	40	104.3	37 Hr.	40	158.8	8 Hr.	4
35 Min.	40	106.4	38 Hr.	40	159.4	9 Hr.	4
40 Min.	40	108.2	39 Hr.	40	160.1	10 Hr.	4
45 Min.	40	107.6	40 Hr.	40	160.6	11-Hr.	4
50 Min.	40	108.4	41 Hr.		at 40 Hrs.	12 Hr.	4
60 Min.	40	109.4	42 Hr.		T	15 Hr.	
70 Min.	40	110.4	43 Hr.			16 Hr.	
ao Min.	40	111.2	44 Hr.			17 Hr.	
90 Min.	40	111.9	45 Hr.			18 Hr.	
100 Min.	40	112.6	46 Hr.			19 Hr.	
130 Min.	40	114.3	47 Hr.			20 Hr.	
160 Min.	40	116.5	48 Hr.			21 Hr.	
190 Min.	40	118.1	49 Hr.			22 Hr.	
220 Min.	40	119.0	50 Hr.			23 Hr.	
250 Min.	40	120.3	81 Hr.			24 Hr.	
280 Min.	40	121,4	52 Hr.			36 Hr.	
5 Hr.	40	122.6	53 Hr.			48 Hr.	
6 Hr.	40	124.0	54 Hr.			72 Hr.	1:

SWL: flow 5.5 gpm

Ariesian pai 22 PSI

Date: 4/15/2002 (tax day)

Notes:

Water was clear and turbid free throught the test. Samples for Chloride and Condutivity were taken at 60 min., 12 Hrs. and 40 Hrs. IOC, VOC, Radionuclaides, and Coliform Bacti, was taken at 24 hours ENCL 189

Kinl	ko's	24H1	Fax	Service	w 161		
-	WAT	ER	BACT	ERI	GICAL	ANAL	YSIS
2	CAL	N F COL	comes, é	tab put	NO ALI BARY NE	AN DENBAR	CORN

if instructions are not followed; sample will be rejected. TIME COLLECTED DATE COLLECTED COUNTY NAME MONTH DAY YEAR IF PUBLIC SYSTEM, COMPLETE: PUBLIC CIRCLE GROUP I.D. No. INDIVIDUAL (serves only 1 residence) NAME OF SYSTEM SPECIFIC LOCATION WHERE SAMPLE COLLECTED (le. kitchen tap & ednool. fire platfon, fountain) TELEPHONE NO. (360)426-3395 DAY EVENING [SYSTEM OWNER / MGR.: (Name) ARCADIA DRILLING, IN GROUND WATER UNDER SURFACE INFLUENCE SURFACE WELL or SPRING PURCHASED or OF OTHER SEND REPORT TO: (Print Full Name, Address and Zip Code)
ARCADIA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON, 98584 WASHINGTON TYPE OF SAMPLE (check only one in this column) ACUTINE PRINKING WATER Chlorinated (Residual: ____Total_ Fillered check treatment Untreated or Other_ REPEAT SAMPLE
Previous colligem presence Previous coliform presence Source # S RAW SOURCE WATER Total Collform Total Coliform NEW CONSTRUCTION OF REPAIRS OTHER (Specify) MARKS eur LABORATORY RESULTS (FOR LAB USE ONLY) METHOD USED MMO MF . MPN CPRG TOTAL COLIFORM E. COLI . 100 ml /100 ml HETEROTROPHIC_ FECAL COUFORM / 100 ml /per mi ANOTHER SAMPLE REQUIRED SAMPLE NOT TESTED BECAUSE: TEST UNSUITABLE BECAUSE: Sample too old ☐ Confluent growth ☐ Wrong container I THTC ☐ incomplete form ☐ Turbid culture ☐ Excess debris DRINKING WATER SAMPLE RESULTS UNSATISFACTORY, Coliforms present Coliforms absent REPEAT E. Coll present E. Coll absent SAMPLES Fecal present Fegal absent SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DATE. TIME RECEIVED RECEIVED BY 089 ACCT. AA004R


Kinko's 24Hr Fax Service 1515 80th St. E. AGEMENT Tacoma, WA 98404 LABORATORIES INC. (253) 531-3121

Ø 009 SEE BACK FOR INSTRUCTIONS

/Samp		4577	Date Co	llected:	4-5-0	2		Source N	IO: NE	1)
ltiple So	ource Nos: NA		3.0		ple Type: J.		Sarry	ple Purpo		
e Recei	ved: 4-6-02	Dat	e Reported		-10-02		pervisor:		1	
				-			^	-11-		
	EFFERSON		e Digested	: NA		Group:	(A) B	Oth	ėr .	_
aple Lo	cation: WELL	HEAD							,	
d Resul	ts & Bill To: ARC	12:0	RILLI	16		Remark	s: A A		7	
				Personal Contraction of the Paris of the Par			AA	004	<u> </u>	
70				SD						
SHE	AW GOT	98	584							
H#	ANALYTES	RESULTS	UNITS	SRL	TRIGGER	MCL	EXC	EEDS	Method/	Analye
		1	GULATED			1.000			114Ctitou/ 2	Litalys
- IA	rsenic	CD.01	mg/l	0.01	0.05	0.05	Trigger?	MCL?	2225	- 40
-	rium	201		0.1	2	0.05	NO	NO	3113B	11/1
-	admium	<0,002	mg/l mg/l	0.002	0.005	2			3113B	110
THE PERSON NAMED IN	hromium	<0.01	mg/l	0.01	0.005	0.005			31138	1
	ercury	< 0.0005	mg/l	0.0005	0.002	0.1			3113B	11
-	elenium	< 0.005	mg/l	0.005	0.002	0.002			3112B	A
	ryllium	<0.002	mg/l	0.003	0.004	0.05			3113B	All
The state of the last of the l	ickel	< 0.04	mg/l	0.04	0.004	0.004			3113B	A
	ntimony	< 0.002	mg/l	0.005	0.006	0.006		_	3111B	-4
	nallium	10.001	mg/l	0.002	0.002	0.002			3113B 3113B	1
C	yanide	< 0.05	mg/l	0.05	0.2	0.2			4500-CNF	- 41
FI	uoride	(0,2	mg/l	0.2	2	4			4110B	LH
N	itrite - N	102	mg/l	0.5	0.5	1	139		4110B	ZHI
N	itrate - N	<0.2	mg/I	0.5	5	10			41108	211
To	otal Nitrate/Nitrite	<0.4	mg/l	0.5	5	10			41108	LIFE
		EPA REGULAT	ED (Second	arv)					11100	-
Ire	on	<0.03	mg/l	0.1	0.3	0.3	NO	110	01740	10
-	anganese	< 0.01	mg/l	0.01	0.05	0.05	NU	10	3111B	-11
	lver	€0.01	mg/l	0.01	0.1	0.1			3111B 3111B	1
	hloride	137	mg/1	20	250	250			4110B	54
	ılfate	45	mg/l	10	250	250			4110B	DW
Zi	inc	< 0.05	mg/1	0.2	5	5			3111B	M
		STATE RE	GULATED							7.01
	odium	73	mg/l	5		1	201		21110	1
	ardness	73	mg/l	10					3111B 2340C	
	onductivity	520	umhos/cm		700	700	NO	NO	2510B	1171
	urbidity	0.5	NTU	0.1	1		1		2130B	III
	olor	<5	color units	5	15	15	V	NO	2120B	CHIC
To	otal Dissolved Solids	N/t	mg/l	150	500	500	-		2540C _	-
		STATE UNF	EGULATEL)						+-
Le	ad	<0.002	mg/l	0.002					3113B	1
C	opper	<0.02	mg/l	0.2					3111B	191/
	TS: FC28		V.						SIMP	1/1/

Ø 007

EHEAVY PEN INSTRUMENTS AREAS ENC (1802



1515 80th St. E. Tacoma, WA 98404 (253) 531-3121

SEE BACK FOR INSTRUCTIONS

b/S	ample No: 089 5	4608	Date (Collected.	4-6-0.	The In	VICIO	ADD		
altic	ole Source Nos: NA	1000		C.	4-6-0.	2	DOI	H Source 1	10: WM	
ho E	Panimad II G			Sam	ple Type: B		Sam	ple Purpo	se: R	
ite n	Received: 4-9-02	I	Date Reporte	d: 4-11	-02	S	upervisor:	GPS		
unt	Y: JEFFERSON	JI	Date Digeste	d: N/		Group:		7		
mpl	e Location: Al Fart	MICI	1 1			Group.	(A) B	Oth	et	
ad B	Paculte & Bill Trans	WEL		4:30	PMJ					
III I	lesults & Bill To: AR	CADIA	DRIL	LING-	•	Remark	s; A	4004	10	
	170 SE	WALK	ER P	DRV	RD	100	/ 1	100	E .	
1-1-1	SHELTON	WA							49-1-	
17.7		-		5584	+			pate		
H#	ANALYTES	RESULTS	UNITS	SRL	TRIGGER	MCL	EXC	EEDS	Method/	Amalan
429		EPA R	EGULATED	Samuel Control			-		TVICTION /	Citalys
	Arsenic	NA	mg/l	0.01	0.05	0.05	Trigger?	MCL?	2005	
	Barium		mg/l	0.1	2	2			3113B	
	Cadmium		mg/1	0.002	0.005	0.005			31138	
	Chromium		mg/l	0.01	0.1	0.1			3113B	
-	Mercury		mg/i	0.0005	0.002	0.002			3113B	3 66
	Selenium		mg/1	0.005	0.05	0.05	-		31128	
)	Beryllium		mg/l	0.003	0.004	0.004			3113B	
	Nickel		mg/l	0.04	0.1	0.1			31138	-
2	Antimony		mg/l	0.005	0.006	0.006			3111B	
3	Thallium		mg/l	0.002	0.002	0.002			3113B	
5_	Cyanide		mg/l	0.05	0.2	0.002			31138	
	Fluoride		mg/l	0.2	2	4	Dente 1	-	4500-CNF	
1	Nitrite - N		mg/l	0.5	0.5	1			4110B	
	Nitrate - N		mg/l	0.5	5	10			41108	
1	Total Nitrate/Nitrite	V	mg/l	0.5	5	10			4110B	-
		EPA REGULA	ATED (Second			10			4110B	1136
	Iron	NA	mg/I	0.1	0.7					
32	Manganese		mg/1	0.01	0.3	0.3			3111B	E N
	Silver	1	mg/l	0.01	0.05	0.05			3111B	
	Chloride	132	mg/1	20	0.1 250	0.1	160	110	3111B	
	Sulfate	NA	mg/1	10	250	250	NO	NO	4110B	GR
	Zinc	_ \	mg/1	0.2	5	250			4110B	
		STATE R	EGULATED			3			3111B	-
	Sodium	MA	mg/l	5			0.00	-		
	Hardness	T,	mg/l	10					3111B	
	Conductivity	44.3	umhos/cm	10	700	700	(la:\	47.0	2340C	
	Turbidity	NA	NTU	0.1	1	700	NO	NO		WMF
	Color		color units	5	15	15			2130B	
	Total Dissolved Solids	V	mg/i	150	500	500			2120B	
		STATE UN	REGULATED		000	200			2540C	
	Lead	NA								
	Copper	·V	mg/l	0.002					3113B	
	NTS: CHLORIDE	30	mg/l	0.2					3111B	



Ø 008

HEAVY PEN NOT WRITE IN SHADED AREAS



1515 80th St. E. Tacoma, WA 98404 (253) 531-3121 SEE BACK FOR INSTRUCTIONS

b/Sar	mple No: 089545	76			4-4-00		DOH	Source N	o: NEW	
ultiple	Source Nos: NA			Samp	ole Type: B		Samp	le Purpos	e: B	
ate Re	ceived: 4-6-02	Da	te Reported:	4-8-	-02-	Su	pervisor:	MM	-	
	JEFFERSON		te Digested:			Group:	A) B	Othe		
-	,								3:	
		LHEA?		ST.		2:00		VIDNIC	FIT 2	
end Re	sults & Bill To: ARC	ADIA	DRIL	LINC	5-	Remark	s: A A	4001	R	
170	SE WALK	THE P	KRD						1	
54	ELTON W		1584							
OH#	ANALYTES	RESULTS	UNITS	SRL	TRIGGER	MCL	EXC	EDS	Method/A	nalust
OIII	THE PART AND			DIC	HOGER				TATERIOU !	nalyst
	T:	711	GULATED	2.07	0.5-		Trigger?	MCL?	,	
4	Arsenic	MIA	mg/l	0.01	0.05	0.05			3113B	1
5	Barium	_	mg/l	0.1	2	2			3113B	
6	Cadmium		mg/l	0.002	0.005	0.005			3113B	
7	Chromium		mg/l	0.01	0.1	0.1			3113B	
11	Mercury		mg/l	0.0005	0.002	0.002	No. al		3112B	
12	Selenium	-	mg/l	0.005	0.05	0.05			3113B	100
10	Beryllium		mg/l	0.003	0.004	0.004			3113B	
11	Nickel		mg/l	0.04	0.1	0.1		17.11	3111B	
12	Antimony		mg/l	0.005	0.006	0.006			3113B	
13	Thallium		mg/l	0.002	0.002	0.002			3113B	
116	Cyanide	2000	mg/l	0.05	0.2	0.2			4500-CNF	
19	Fluoride		mg/l	0.2	2	4			4110B	
114	Nitrite - N		mg/l	0.5	0.5	1			41108	
20	Nitrate - N		mg/l	0.5	5	10	254	1	4110B	
161	Total Nitrate/Nitrite	<u> </u>	mg/l	0.5	5	10			4110B	-
		EPA REGULA	TED (Second	ary)	5.0	4, 200				
8	Iron	NA	mg/l	0.1	0.3	0.3			31118	100
10 ·	Manganese		mg/l	_0.01	0.05	0.05			31118	
13	Silver	4	mg/l	0.01	0.1	0.1			3111B	14 4
21	Chloride	138	mg/1	20	250	250	حمر	NO	4110B	Dise
22	Sulfate '	MA	mg/1	10	250	250			4110B	
24	Zinc	4.00	N14101 2	0.2	5.	5			31118	
			EGULATED		-					MT.
14	Sodium	NA	mg/l	5					3111B	
15	Hardness	1	mg/l	10					2340C	V. 400
16	Conductivity	535	umhos/cm	Charles and the Contract of th	700	700	NO	NU	25108	440
17	Turbidity	NIA	NTU	0.1	1	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1			2130B	
18	Color		color units		15	15		1982, 1994	2120B	
26	Total Dissolved Solids		mg/l .	150	500	500			2540C	
			REGULATE	D						1
9	Lead	NA	mg/1	0.002					3113B	
23	Copper	ale	mg/1	0.2					3111B	+



1515 80th St. E. Tacoma, WA 98404 (253) 531-3121 SEE BACK FOR INSTRUCTIONS

..2,3

Sar	mple No: 089545	76	Date Co	llected:	4-4-02		DOH	Source N	10: NEW)
	Source Nos: NA			Sam	ple Type: 🔂		Samp	ole Purpos	e: B	
_		Da	to Reported	4-0	ple Type: B	Su	pervisor:			
Ke	ceived: 4-6-02									
ty:	JEFFERSON	Da	te Digested:			Group:	A B			
ole	Location: WE	LHEAT	S TE	ST .	2 (12	1:00 A	AM N	NIDNIC	SITT)	
Re	sults & Bill To: AR	CADIO	0011	141	_	Remarks		1004		
					<u>, , , , , , , , , , , , , , , , , , , </u>			1001		
0	SE WAL	KER P	KKD							
H	ELTON W	A 98	5584							
#	ANALYTES	RESULTS	UNITS	SRL	TRIGGER	MCL	EXC	EEDS	Method/A	nalyst
		EPA RE	GULATED	15. 12.6			Trigger?	MCL?		
	Arsenic	NIA	mg/l	0.01	0.05	0.05	88		3113B	
_	Barium	100	mg/l	0.1	2	2			3113B	
	Cadmium		mg/l	0.002	0.005	0.005			3113B	
_	Chromium		mg/l	0.002	0.003	0.003			3113B	
_		1000	mg/l	0.0005	0.002	0.002			3113B 3112B	-
_	Mercury Selenium			0.0005	0.002	0.002			3112B	-
_			mg/l	0.003	0.004	0.004			3113B	
	Beryllium Nickel		mg/l	0.003	0.004	0.004			3111B	1000
-			mg/l	0.005	0.006	0.006			3113B	-
	Antimony		mg/l	0.003	0.002	0.002				-
	Thallium		mg/l	0.002	0.002	0.002			3113B 4500-CNF	+
	Cyanide Fluoride		mg/l	0.03	2	4			4110B	-
	Nitrite - N		mg/l	0.2	0.5	1			4110B	
			mg/l	0.5	5	10				+-
	Nitrate - N		mg/l	0.5	5	10			4110B	+
_	Total Nitrate/Nitrite	EDA DECLUI A	mg/l		3	1 10			4110B	-
		EPA REGULA		7,						138
	Iron	NA	mg/l	0.1	0.3	0.3			3111B	-
	Manganese		mg/l	0.01	0.05	0.05			3111B	
	Silver	4	mg/l	0.01	0.1	0.1			3111B	+-
	Chloride	138	mg/1	20	250	250	NO	NO	4110B	3
	Sulfate	MA	mg/1	10	250	250			4110B	-
	Zinc	1 +	mg/1	0.2	5	5			3111B	+
			EGULATED							
	Sodium	NA	mg/l	5					3111B	
	Hardness	1	mg/l	10					2340C	
	Conductivity	535	umhos/cm		700	700	NO	NU	2510B	4
	Turbidity	NA	NTU	0.1	1				2130B	
	Color		color units		15	15			2120B	
,	Total Dissolved Solids		mg/l	150	500	500			2540C	
		STATE UN	IREGULATE	0						
	Lead	NA	mg/l	0.002	100000				3113B	
	Copper		mg/l	0.2					3111B	1



1515 80th St. E. Tacoma, WA 98404 (253) 531-3121

SEE BACK FOR INSTRUCTIONS

mple No: 0895	4577	Date Co	llected:	4-5-00	2	DOH	Source N	lo: NEU	O
e Source Nos: A / A			Sam	ple Type: R		Samp	ole Purpos		
eceived: 4-12-02	Dat	e Reported		-10-02	Su	pervisor:	400		
1000		-					Oth		
JEFFERSON	Dat	e Digested	· NA		Group:	A B	Otne	er	
e Location: WELL	HEAD								
Lesults & Bill To: ARC	ADIA D	RILLIA	10-		Remark	s: AA	004	R	
			ZD			-/-	CO		
A			<u> </u>		-			•	
HELTON WA	10	584							
ANALYTES	RESULTS	UNITS	SRL	TRIGGER	MCL	EXC	EEDS	Method/A	Analys
	EPA REC	GULATED				Trigger?	MCL?		× Territoria
Arsenic	<0.01	mg/l	0.01	0.05	0.05	NO	NO	3113B	AV
Barium	<0.i	mg/l	0.1	2	2			3113B	1
Cadmium	<0.002	mg/l	0.002	0.005	0.005			3113B	M
Chromium	<0.01	mg/l	0.01	0.1	0.1			3113B	A
Mercury	<0.0005	mg/l	0.0005	0.002	0.002			3112B	1
Selenium	<0.005	mg/l	0.005	0.05	0.05			3113B	1
Beryllium	<0.002	mg/l	0.003	0.004	0.004			3113B	U
Nickel	< 0.04	mg/l	0.04	0.1	0.1			3111B	1
Antimony	< 0.002	mg/l	0.005	0.006	0.006			3113B	A
Thallium	LP.001	mg/l	0.002	0.002	0.002			3113B	A
Cyanide	< 0.05	mg/l	0.05	0.2	0.2			4500-CNF	1
Fluoride	(0,2)	mg/l	0.2	2	4		-	4110B	TH
Nitrite - N	102	mg/l	0.5	0.5	1			4110B	LHI
Nitrate - N	(0.2)	mg/l	0.5	5	10	7		4110B	LH
Total Nitrate/Nitrite	1 <0.4	mg/l	0.5	5	10			4110B	LH
	EPA REGULAT	TED (Second	ary)					- 1965. W	
Iron	<0.03	mg/l	0.1	0.3	0.3	NO	NO	3111B	11
Manganese	<0.01	mg/l	0.01	0.05	0.05	1	1	3111B	1
Silver		mg/l	0.01	0.1	0.1			3111B	121
Chloride	137	mg/1	20	250	250			4110B	Dw
Sulfate	45	mg/1	10	250	250			4110B	on
Zinc	<0.05	mg/1	0.2	5	5			3111B	110
	STATE RE	GULATED							111
Sodium	73	mg/l	5		desire			3111B	M
Hardness	73	mg/l	10					2340C	on
Conductivity	520	umhos/cm		700	700	NO	NO	2510B	1111
Turbidity	0.3	NTU	0.1	1	700	1		2130B	ill
Color	<5	color units	5	15	15		NO	2130B	MI
Total Dissolved Solids	NA	mg/l	150	500	500			2540C _	11
	STATE UNI				1 200		-	20100 -	
Lead	<0.002	mg/l	0.002					21120	1
Copper	<0,02		0.002					3113B	M
Copper	1 010 2	mg/l	0.2					3111B	1/1



1515 80th St. E. Tacoma, WA 98404 (253) 531-3121



ar	mple No: 089 54	608	Date Co	llected:	4-6-02		DOH	Source N	o: WH	
	Source Nos: NA				ple Type: B		Samp	le Purpos	e: 13	
_	ceived: 4-9-02	Dat	e Reported:			Su	pervisor: (SPS		
	VT 1		e Digested:			Group:	(A) B	Othe	r	
-	0011010			NA		- Toup.	<u> </u>			
	Location: NEW	WELL	. (4	1:30	PMJ					
Re	sults & Bill To: ARC	ADIA	DRILL	ING		Remark	s: A/	4004	LR	
_	170 SE	WALKE	RPA	RK	RD					
-					1					
_	SHELTON	WA	T	586	<u> </u>					
	ANALYTES	RESULTS	UNITS	SRL	TRIGGER	MCL	EXCE	EEDS	Method/	Analyst
		EPA REC	GULATED				Trigger?	MCL?		
	Arsenic	WA	mg/l	0.01	0.05	0.05			3113B	
	Barium	1.	mg/l	0.1	2	2			3113B	
	Cadmium		mg/l	0.002	0.005	0.005			3113B	
	Chromium		mg/l	0.01	0.1	0.1			3113B	
	Mercury		mg/l	0.0005	0.002	0.002			3112B	
	Selenium		mg/l	0.005	0.05	0.05			3113B	
	Beryllium		mg/l	0.003	0.004	0.004			3113B	
	Nickel		mg/l	0.04	0.1	0.1			3111B	
	Antimony		mg/l	0.005	0.006	0.006			3113B	
	Thallium		mg/l	0.002	0.002	0.002			3113B	
	Cyanide		mg/l	0.05	0.2	0.2			4500-CNI	F
	Fluoride		mg/l	0.2	2	4			4110B	
	Nitrite - N		mg/l	0.5	0.5	1			4110B	
	Nitrate - N		mg/l	0.5	5	10			4110B	
	Total Nitrate/Nitrite	V	mg/l	0.5	5	10			4110B	
		EPA REGULA	TED (Second	ary)						
	Iron	NA	mg/l	0.1	0.3	0.3		11 3.34	3111B	
	Manganese		mg/l	0.01	0.05	0.05		4.5	3111B	
	Silver	V	mg/l	0.01	0.1	0.1			3111B	-
	Chloride	132	mg/1	20	250	250	NO	NO	4110B	GP.
	Sulfate	NA	mg/1	10	250	250			4110B	
	Zinc	1	mg/1	0.2	5	5			3111B	
		STATE R	EGULATED							
	Sodium	NA	mg/l	5		The second	1 1 1		3111B	
	Hardness	V	mg/l	10					2340C	
	Conductivity	44.3	umhos/cm		700	700	NO	NO	2510B	VVMI
	Turbidity	NA	NTU	0.1	1				2130B	
	Color		color units		15	15			2120B	
	Total Dissolved Solids	1	mg/l	150	500	500	1 1 1		2540C	
		STATE UN	REGULATEI					A		
_	Lead	NA	mg/l	0.002					3113B	
_	Copper	1	mg/l	0.002					3111B	15
_	Copper	1	1116/1	0.4					JIIID	(1)

Individual I.D. No.	DATE COLLECTED TIME COLLECTED COUNTY NAME COUNTY NAM	3 SAMPLE COL	LECTION, READ INST	OGICAL ANA NS ON BACK OF GOLDENR A sample will be rejected.	CD COPY
TYPEOF SYSTEM IPPUBLIC INDIVIDUAL (Servess only 1 residence) I.D. No. III I I I I I I I I I I I I I I I I I	TYPE OF SYSTEM IPUBLIC INDIVIDUAL (serviso only 1 residence) NAME OF SYSTEM NAME OF SYSTEM NAME OF SYSTEM NAME OF SYSTEM SPECIFL LOCATION WHERE SAMPLE COLLECTED TELEPHONE NO. DAY (360) 4 26-3395 WELL HEAL SPECIFL LOCATION WHERE SAMPLE COLLECTED TELEPHONE NO. DAY (360) 4 26-3395 WELL HEAL SENDING GROUND WATER UNDER SURFACE NUMBER / MGR.: (Name) ACADIA DRILLING, IN SOURCE TYPE GROUND WATER UNDER SURFACE NITLERING SEND REPORT TO: (Print Flield) GOMBINATION SEND REPORT TO: (Print Flield) SEND REPORT TO: (Print Flield) SEND REPORT TO: (Print Flield) TOTAL COLLING METHOD USED METHOD USED METHOD USED METHOD USED METHOD USED METHOD USED ANOTHER SAMPLE RECUIRED SAMPLE NOT TESTED BECAUSE: SEND REPORT TO: (Print Flield) DRINKING WATER SAMPLE RECUIRED SAMPLE NOT TESTED BECAUSE: SEND REPORT TO: (Print Flield) REPORT TO: (Print Flield) SEND REPORT TO: (Print Flield) REPORT TO: (Print Flield) SEND REPORT TO: (Print Flield) REPORT TO: (Print Flield) SEND REPORT TO: (Print Flield) REPORT TO: (Print Flield) SEND REPORT TO: (Print Flield) REPORT TO: (Print Flield) REPORT TO: (Print Flield) SEND REPORT TO: (Print Flield) REPORT TO: (Print Flield) REPORT TO: (Print Flield) SEND REPORT TO: (Print Flield) REPORT TO: (Print Flield) REPORT TO: (Print Flield) REPOR	DATE COLLEC	TIME (COLLECTED COUNTY	NAME
DATE REPORTED I.D. No.	DATE REPORTED NAME OF SYSTEM O'UMDIC ANAL RACKS AGG. SECORE LOCATION WHERE SAMPLE COLLECTED (to, kitchen lab g) school, five liation, fountain) NAME OF SYSTEM O'UMDIC ANAL RACKS AGG. SECORE LOCATION WHERE SAMPLE COLLECTED (to, kitchen lab g) school, five liation, fountain) DAY (360) 426-3395 EVENING DAY (360) 426-3395 EVENING SYSTEM OWNER/ MGR.: (Name) ARCADIA DRILLING, IN SOURCE TYPE GROUND WATER UNDER SURPACE INFLUENCE SURPACE WELL or SPRING PURCHASED or COMBINAT OF O'OTHER SEND REPORT TO: (Print Full Name, Address and Zip Code) ARCADIA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON, WASHINGTON 98584 TYPE OF SAMPLE (check only one in this column) ACUTINE FINKING WATER OBJECT OF SPRING PREVIOUS COLIFORM FINE SHOP COLLECTED OBJECT OF SPRING PREVIOUS COLIFORM FINE SHOP COLLECTED OBJECT OF SAMPLE WATER OBJECT OF SAMPLE WATER SOURCE WATE	9/3/		7 00	TYCRSON
SPECIFIC LOCATION WHERE SAMPLE COLLECTED SPECIFIC LOCATION WHERE SAMPLE COLLECTED (ite. kinchen lap & gebood. five blation, fountain) SPECIFIC LOCATION WHERE SAMPLE COLLECTED (ite. kinchen lap & gebood. five blation, fountain) SAMPLE COLLECTED BY: (Name) SAMPLE REPORT TO: (Print Full Name, Address and Zip Code) ARCADIA DRILLING, IN SEND REPORT TO: (Print Full Name, Address and Zip Code) ARCADIA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON, TYPE OF SAMPLE (check only one in this column) ACUTINE SAMPLE (check only one in this column) SAMPLE NOTHER (Specify) TOTAL COLIFORM TOTHER (Specify) METHOD USED MF MPN PA MMO CPRG TOTAL COLIFORM TOTAL COLIFORM TOO mI FECAL COLIFORM TOTAL CO	SPECIFÉ LOCATION WHERE SAMPLE COLLECTED SPECIFÉ LOCATION WHERE SAMPLE COLLECTED (ile, kitchen lab & gelbool, the flation, foundain) SPECIFÉ LOCATION WHERE SAMPLE COLLECTED (ile, kitchen lab & gelbool, the flation, foundain) SAMPLE COLLECTED BY: (Name) SAMPLE COLLECTED BY: (Name) SAMPLE COLLECTED BY: (Name) SAMPLE COLLECTED BY: (Name) SPECIFÉ GROUND WATER UNDER SURFACE INFLUENCE SURFACE WELL FIELD SPRING PURCHASED OF COMBINAT OF OTHER SPRING PURCHASED OF COMBINAT NTERTIE OF COMBINAT OF OTHER SEND REPORT TO: (Prin Full Name, Address and Zip Code) ARCADIA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON, WASHINGTON 98584 TYPE OF SAMPLE (check only one in this column) AQUITINE TYPE OF SAMPLE (check only one in this column) AQUITINE TRINKING WATER Chlorinated (Residual: Total Free) Chlorinated (Residual: Total Free) Chlorinated (Residual: Total Free) Chlorinated or Other Previous coliform presence Date Da	PUBLIC INDIVIDUAL	I.D. No.	1 1 9 6 K	CIRCLE GROU
DAY	DAY (360)426-3395 DAY (360)4426-3395 DA	Dympic C		PACES ACT	d. 1
SAMPLE COLLECTED BY: (Name) RCADA: A DELITING SYSTEM OWNER / MGR.: (Name) ARCADIA DRILLING, IN SOURCE TYPE GROUND WATER UNDER SURFACE INFLUENCE SURFACE WELL or SPRING PURCHASED or COMBINATION OF RESULTS SEND REPORT TO: (Print Full Name, Address and Zip Code) ARCADIA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON,	SAMPLE COLLECTED BY: (Name) RCADIA DELITING SYSTEM OWNER / MGR.: (Name) ARCADIA DRILLING, IN SOURCE TYPE GROUND WATER UNDER SURFACE INFLUENCE SURFACE MELL OF OTHER SURFACE INFLUENCE SURFACE MELL OF OTHER SEND REPORT TO: (Print Full Name, Address and Zip Code) ARCADIA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON,				426-3395
ARCADIA DRILLING, IN SOURCE TYPE GROUND WATER UNDER SURFACE INFLUENCE SURFACE WELL or SPRING PURICHASED or COMBINAT INTERTILE SURFACE WELL or SPRING PURICHASED or COMBINAT OR OTHER SEND REPORT TO: (Print Full Name, Address and Zip Code) ARCADIA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON, WASHINGTON 98584 TYPE OF SAMPLE (check only one in this column) PROUTINE Chlorinated (Residual: Total Free) Previous coliform presence Previous coliform presence Date Free) Previous coliform Free) Previous coliform Free) Previous coliform Free) Previous coliform Free) Previous coliform	ARCADIA DRILLING, IN SOURCE TYPE GROUND WATER UNDER SURFACE INFLUENCE SURFACE WELL or SPRING PURCHASED or COMBINATION OF OTHER SEND REPORT TO: (Print Full Name, Address and Zip Code) ARCADIA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON, WASHINGTON 98584 TYPE OF SAMPLE (check only one in this column) ADUTINE Chlorinated (Residual: Total Free) Previous coliform presence Lab # Total Free) Previous coliform presence Date Previous coliform Precal Coliform Pre	Well 1	tener	EVENING ()	
SOURCE TYPE GROUND WATER UNDER SURFACE INFLUENCE SURFACE WELL or SPRING PURCHASED or COMBINATION SURFACE WELL FIELD SPRING PURCHASED OR COMBINATION OF RESULTS SEND REPORT TO: (Print Full Name, Address and Zip Code) ARCADIA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON, WASHINGTON 98584 TYPE OF SAMPLE (check only one in this column) POUTINE Chlorinated (Residual: Total Free) Filtered Untreated or Other Previous coliform presence Previous coliform Previous	SOURCE TYPE GROUND WATER UNDER SURFACE INFLUENCE SURFACE WELL or SPRING PURCHASED or COMBINATION OF RESULTS SEND REPORT TO: (Print Full Name, Address and Zip Code) ARCADIA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON, WASHINGTON 98584 TYPE OF SAMPLE (check only one in this column) PROUTINE Chlorinated (Residual: Total Free) TRINKING WATER Filtered Unitreated or Other Previous coliform presence Pate Previous coliform presence Previous coliform	1 . 1	BY: (Name)		
SEND REPORT TO: (Print Full Name, Address and Zip Code) ARCADITA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON, WASHINGTON 98584 TYPE OF SAMPLE (check only one in this column) ROUTINE	SEND REPORT TO: (Print Full Name, Address and Zip Code) ARCADITA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON, WASHINGTON 98584 TYPE OF SAMPLE (check only one in this column) FOUTINE RINKING WATER Check treatment Grillered Check treatment Check tre		GROUND WATER UN	DER SURFACE INFLUE	NCE
ARCADIA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON,	ARCADIA DRILLING, INC SE 170 WALKER PARK ROAD SHELTON,		WELL FIELD	INTERTIE	
TYPE OF SAMPLE (check only one in this column) AOUTINE	TYPE OF SAMPLE (check only one in this column) AOUTINE	ARCADIA DRI	LLING, INC		
TYPE OF SAMPLE (check only one in this column) AOUTINE	TYPE OF SAMPLE (check only one in this column) AOUTINE	SHELTON			98584
METHOD USED MF MPN PA MMO CPRG TOTAL COLIFORM 100 ml E. COLI 100 ml HETEROTROPHIC /pe ANOTHER SAMPLE REQUIRED SAMPLE NOT TESTED BECAUSE: TEST UNSUITABLE BECAUSE Confluent growth TNTC Turbid culture Excess debris DRINKING WAT ER SAMPLE RESULTS DRINKING WAT ER SAMPLE RESULTS DRINKING WAT ER SAMPLE RESULTS REPEAT E. Coli present E. Coli absent REPEAT Fecal absent Fecal absent SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DAT E. TIME RECEIVED RECEIVED BY DATE REPORTED ROUTE ACCT. #	METHOD USED MF MPN PA MMO CPRG TOTAL COLIFORM 100 ml E. COLI 100 ml HETEROTROPHIC /pe ANOTHER SAMPLE REQUIRED SAMPLE NOT TESTED BECAUSE: TEST UNSUITABLE BECAUSE Confluent growth TNTC Turbid culture Excess debris DRINKING WAT ER SAMPLE RESULTS DRINKING WAT ER SAMPLE RESULTS DRINKING WAT ER SAMPLE RESULTS REPEAT E. Coli present E. Coli absent SAMPLES REQUIRED Fecal present Fecal absent SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DAT E. TIME RECEIVED RECEIVED BY DATE REPORTED ACCT. #	Previous coli	form presence Date CE WATER Sou TRUCTION or REPAIR ecify) W Not	rce # S S	Fecal Coliform
MF MPN PA MMO CPRG TOTAL COLIFORM/100 ml FECAL COLIFORM//100 ml FECAL CO	MF MPN PA MMO CPRG TOTAL COLIFORM/100 ml FECAL COLIFORM//100 ml FECAL C				,
ANOTHER SAMPLE REQUIRED SAMPLE NOT TESTED BECAUSE: Sample too old Wrong container Incomplete form DRINKING WATER SAMPLE RESULTS Excess debris DRINKING WATER SAMPLE RESULTS DRINKING WATER SAMPLE RESULTS DRINKING WATER SAMPLE RESULTS DATISFACTORY, Coliforms present REPEAT SAMPLES REQUIRED Fecal present SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DATE, TIME RECEIVED DATE REPORTED DATE REPORTED DATE REPORTED ACCT. #	ANOTHER SAMPLE REQUIRED SAMPLE NOT TESTED BECAUSE: Sample too old Wrong container Incomplete form DRINKING WATER SAMPLE RESULTS DRINKING WATER SAMPLE RESULTS UNSATISFACTORY, Coliforms present REPEAT SAMPLES REQUIRED Fecal present SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS DATE, TIME RECEIVED DATE REPORTED ACCT. #	. MF			CPRG
ANOTHER SAMPLE REQUIRED SAMPLE NOT TESTED BECAUSE: Sample too old Wrong container Incomplete form DRINKING WATER SAMPLE RESULTS UNSATISFACTORY, Coliforms present REPEAT SAMPLES REQUIRED Fecal present SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS DATE, TIME RECEIVED DATE REPORTED ACCT. #	ANOTHER SAMPLE REQUIRED SAMPLE NOT TESTED BECAUSE: Sample too old Wrong container Incomplete form DRINKING WATER SAMPLE RESULTS DRINKING WATER SAMPLE RESULTS UNSATISFACTORY, Coliforms present REPEAT SAMPLES REQUIRED Fecal present SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DATE, TIME RECEIVED DATE REPORTED DATE REPORTED ACCT. #	TOTAL COLIFORM_ FECAL COLIFORM_	/100 ml	E. COLI.	/100 ml
Sample too old Wrong container Incomplete form DRINKING WATER SAMPLE RESULTS DRINKING WATER SAMPLE RESULTS UNSATISFACTORY, Coliforms present REPEAT SAMPLES REQUIRED Fecal present E. Coli absent SAMPLES REQUIRED Fecal present Fecal absent SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DATE, TIME RECEIVED RECEIVED BY DATE REPORTED ROUTE ACCT. #	Sample too old Wrong container Incomplete form DRINKING WATER SAMPLE RESULTS DRINKING WATER SAMPLE RESULTS UNSATISFACTORY, Coliforms present REPEAT SAMPLES REQUIRED Fecal present SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DATE, TIME RECEIVED RECEIVED BY DATE REPORTED DATE REPORTED ROUTE Confluent growth TNTC TUTDIC Culture Excess debris SATISFACTORY, Coliforms absent Fecal absent RECEIVED BY RECEIVED BY DATE REPORTED ROUTE ACCT. #		ANOTHER S	AMPLE REQUIRED	
UNSATISFACTORY, Coliforms present REPEAT SAMPLES REQUIRED Fecal present SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DATE, TIME RECEIVED DATE REPORTED ACCT. #	UNSATISFACTORY, Coliforms present REPEAT SAMPLES REQUIRED Fecal present SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DATE, TIME RECEIVED DATE REPORTED DATE REPORTED ACCT. #	☐ Sample too old ☐ Wrong contains	ED BECAUSE:	TEST	onfluent growth NTC urbid culture
REPEAT SAMPLES REQUIRED E. Coli present E. Coli absent SAMPLES REQUIRED Fecal present Fecal absent SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DATE, TIME RECEIVED RECEIVED BY ACCT. #	REPEAT SAMPLES E. Coli present E. Coli absent SAMPLES REQUIRED Fecal present Fecal absent SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DATE, TIME RECEIVED RECEIVED BY DATE REPORTED ROUTE ACCT. #	UNSATISFACT			
SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DATE, TIME RECEIVED RECEIVED BY DATE REPORTED ROUTE ACCT. #	SEE REVERSE SIDE OF GREEN COPY FOR EXPLANATION OF RESULTS LAB NO. DATE, TIME RECEIVED RECEIVED BY DATE REPORTED ROUTE ACCT. #	REPEAT SAMPLES	E. Coli present	E. Coli absent	Coliforms absent
089 6 1945 4-6 02 6 KM DC	089 6 1945 4-6 02 6 KM DC			COPY FOR EXPLANA	ATION OF RESULTS
DATE REPORTED ROUTE ACCT. #	DATE REPORTED ROUTE ACCT. #			E, TIME RECEIVED	RECEIVED BY
	AA004R	DATE REPORTED	140 14		ACCT. #

3 SAMPLE COLLE	CTION INST	RUCTIONS O				'SIS	(3
DATE COLLECTE MONTH / DAY /	ons are not fo	ME COLLE	CTE	will be	NTY NA	ME	
TYPE-OF SYSTEM	IF PUBLIC ST		MP OMP	LETE:	ett	erson	J
PUBLIC INDIVIDUAL (serves only 1 residence)	I.D. No.	11	1	96	M	CIRC	E GROUP B
NAME OF SYSTEM SPECIFIC LOCATION WHERE S	AMPLE COLLECTE	(RAC	_	HONE NO	dd.	1	
(ie, kitchen tap @ school, fire	station, fountain)	_ D	AY	, 36	0 142	6-3395	
SAMPLE COLLECTED B	Y: (Name)		VENI (STE) R/MGI	R.: (Name)	
ARCADIA De	illing.					LING,	IN
SURFACE WE WE	LL FIELD	SPRING		PURCHA	SED or	CON	MBINATIO THER
SEND REPORT TO: (Prin			Zip	Code)			
SE 170 WALKER	R PARK RO	DAD				0050	Λ
TYPE OF SAMPLE (chec	П					N 9858	
Check treatmer REPEAT SAMP Previous colifor Previous colifor Previous Colifor RAW SOURCE NEW CONSTR	PLE rm presence rm presence WATER UCTION or REI					Total Colifo	
Hew WEI	i No	10	N	Li	YE	!!	
LA	ABORATORY R				NLY)		
		METHOD (JSEL)			
MF I	MPN			1	1		
	1	PA		MMC)	CPRG	
TOTAL COLIFORM FECAL COLIFORM	/ 100 ml	PA		E. CO		CPRG /100 PHIC	
TOTAL COLIFORM	/ 100 ml	PA R SAMPLI	E RE	E. CO		/100	
TOTAL COLIFORM	/ 100 ml		E RE	E. COI HETEI QUIRED TES	ROTRO	/100 PHIC/ UITABLE BEent growth	/per n
TOTAL COLIFORM FECAL COLIFORM SAMPLE NOT TESTED Sample too old Wrong container Incomplete form	ANOTHE BECAUSE: DRINKING V	R SAMPLI		E. COO HETEI QUIRED	ET UNSI Conflue TNTC Turbid Excess	/100 PHIC/100 UITABLE BEent growth culture debris	/per n
TOTAL COLIFORM FECAL COLIFORM SAMPLE NOT TESTED Sample too old Wrong container Incomplete form	ANOTHE BECAUSE: DRINKING V	R SAMPLI	MPL E. Co	E. COO HETEI QUIRED	ET UNSI Conflue TNTC Turbid Excess	/100 PHIC/ UITABLE BEent growth	/per n
TOTAL COLIFORM	DRINKING NRY, Coliforms p G. Coli prese Fecal presents	R SAMPLI WATER SA resent nt	MPL E. Co For Form	E. CO HETE: QUIRED TES D E RESUL li absent absent R EXPLAN	TS	JITABLE BE ent growth culture debris	TORY, absent
TOTAL COLIFORM	DRINKING NRY, Coliforms p G. Coli prese Fecal presents	R SAMPLI WATER SA resent nt	MPL E. Co For Form	E. COO HETE: QUIRED TES CERSULI Ii absent absent R EXPLAN CEIVED	TS	PHIC	TORY, absent

Arcadia Drilling, Inc.

Customer: Canal View Tracts

310713 Hwy 101 Brinnon, WA 98302 Contact: Dave Andreson/ Dick Wasson

Project: Deep Well Drill and Test

Phone: (253) 852-3687 Dave Phone: (206) 242-2072 Dick

Fax: E-mall Cell:

Date of Test; 4/5 - 4/6 2002

Pump Test	Data:		All Measure
T16.45	gallons per min,		
TIME	GPM	LEVEL	
10 Sec.	40	3.5	1 1
20 Sec.	40	6.0	-
30 Sec.		9,3	1 }
40 Sec.	40	16,0	l 1
50 Sec.	40	20.0	l -
60 Sec.		24.2	1 }
70 Sec. 80 Sec.	40	28.6	l -
90 Sec.	40	31.9	·
	40	35.0	1 -
100 Sec.	40	38.0	
110 Sec.	40	40.8 42.9	l -
2 Min. 2.5 Min.	40	50.9	1 }
3 Min.		56.3	l 1-
3.5 Min.	40	61.5	l t
4 Min.	40	65.7	Birth 100
4.5 Min.	40	69.7	
5 Min.		72.9	<i>\$</i>
6 Min.	40	78.5	
7 Min.	40	82.5	2 1425
8 Min.	40	86.2	
9 Min.		89.0	
10 Min.	40	91.2	
11 Min.		93,3	
12 Min.		94.8	
13 Min.	40	95.7	
14 Min.	40	97.1	
15 Min.		98.1	
20 Min.		101.1	
25 Min.		102.9	
30 Min.		104.3	
35 Min.		105.4	
40 Min.	THE RESERVE AND PERSONS ASSESSMENT	106.2	
45 Min.	40	107,6	
50 Min.	40	108.4	
60 Min.	40	109.4	
70 Min.		110.4	4
80 Min.	THE RESERVE AND ADDRESS OF THE PERSON NAMED AND ADDRESS OF THE	111.2	
90 Min.	40	111.9	
100 Min.		112.6	4
130 Min.		114.3	
160 Min.	THE RESERVE AND ADDRESS OF THE PARTY OF THE	116.5	
190 Min.	40	118,1	
220 Min.		119.0	4 +
250 Min.		120.3	
280 Min.	THE RESERVE AND DESCRIPTION ASSESSMENT	121.4	4
5 Hr	40	122 6	

ements are	rom top of c	asing	
	gations per min.		
TIME	GPM	LEVEL	
7 Hr.	40	125.7	
8 Hr.	40	127.5	
9 Hr.	40	128.5	
10 Hr.	40	129.6	
11 Hr.	40	131.0	
12 Hr.	40	132.2	
13 Hr.	40	133.5	
14 Hr.	40	135.6	
15 Hr.	40	136.4	Ĺ
18 Hr.	40	137.6	
17 Hr.	40	138.5	
18 Hr.	40	139.6	
19 Hr.	40	140.3	
20 Hr.	40	140.9	
21 Hr.:	40	141.9	1
22 Hr.	40	143.0	1
23 Hr.	40	143.9	
24 Hr.	40	144.9	
25 Hr.	40	147.8	
26 Hr.	40	149,9	1
27 Hr.	40	151.9	1
28 Hr.	40	152.6	1
29 Hr.	40	153.4	
30 Hr.	40	154.2	
31 Hr. 32 Hr.	40	155.4	
33 Hr.		156.0	
	40	156,5	
34 Hr.	40	157.0	
35 Hr. 36 Hr.	40	157.5	
37 Hr.	40	158.0 158.8	
38 Hr.	40	159.4	
39 Hr.	40	160.1	
40 Hr.	40	160.6	
41 Hr.			1
42 Hr.			
43 Hr.	For Charles		100
44 Hr.	The state of the s		
45 Hr.		O THE REAL PROPERTY.	
46 Hr.			
47 Hr.			
48 Hr.		100 may 120	
49 Hr.	1,425,64		
60 Hr.			
51 Hr.			
52 Hr.		148	

Recovery D	ata:
	foot-10ths
TIME	LEVEL,
10 Sec.	
20 Sec.	
30 Sec.	137.0
40 Sec.	
50 Soc.	125.0
60 Sec.	121.0
2 Min.	113.0
3 Min.	105.0
4 Mln.	99.5
5 Min.	92.8
6 Min.	88.1
7 Min.	83.7
8 Min.	81.0
9 Min.	79.3
10 Min.	77.4
11 Min.	76.1
12 Min.	75.0
13 Min.	74.0
14 Min.	
15 Min.	
20 Min.	
25 Min.	
30 Min.	67,8
1 Hr.	62.9
2 Hr.	59.1
3 Hr.	53.5
4 Hr.	51.0
5 Hr,	49.4
8 Hr.	
7 Hr.	48,4
8 Hr.	
9 Hr.	
10 Hr.	43.2
11 Hr.	42.9
12 Hr.	41.8
15 Hr.	
16 Hr.	
17 Hr.	
18 Hr.	
19 Hr.	
20 Hr.	
21 Hr.	
22 Hr. 23 Hr.	
24 Hr.	
36 Hr.	
48 Hr.	
48 Hr.	
/2 HI.	12.5

SWL: flow 5.5 gpm Artesian pai 22 PSI

5 Hr.

6 Hr.

Date: 4/15/2002 (tax day)

40

Notes:

122.6

124.0

Water was clear and turbid free throught the test, Samples for Chloride and Condutivity were taken at 60 min., 12 Hrs. and 40 Hrs. IOC, VOC. Radionucleides, and Coliform Bacti, was taken at 24 hours

170 SE Walker Park Road Shelton, WA 98584 (360) 426-3395 voice (360) 426-1455 fax







Beach Club House Lane Water System (#1196M) - Source Approval 16 December 2002


Enclosure 15 (Construction Details)

- 1. The purpose of this inclosure is to provide information on the pump and well head.
- 2. TDH.
 - A. Static Head. Assume that pumping the well stabilizes at 150 feet. Assume that the storage tank is 25 feet higher than the well head. Total Static head. 175 feet.
 - B. Dynamic Head. Assume flow of 32 gpm in a 11/2 inch plastic riser pipe (from practical engineering information use 16.9 feet for every 100 feet for 150 feet is 25 feet of lost.
 - C. Misc head lost between well site- pump house and water tank, assume 10 feet.
 - D. TDH approximately 210 feet.
- 3. Pump Selection. The steep draw down condition would indicate that a pump with a flat pump curve would best fit this situation. A flow-regulating valve should also be installed in line to prevent any up thrust damage to the pump. Enclosed are pump recommendation from the driller. 2HP submersible pump.
- 4. The new well will be plumbed into the existing system. The well will use a pitless adapter, with required vent and access. A new check valve will be installed inside of the pump house and on top of the pump. Other controls, booster pumps, meters, chlorination, and pressure tanks will be existing system facilities.
- 5. The pump will operate off of existing floats located in the water tank.
- 6. The new pump will have a separate breaker installed in the existing exterior panel to power the new pump submersible pump.












TER FACILITIES INVENTORY (WFL)

Read Instructions on back before completing

STEM ID NO. 2. COUNTY	ingle Tree	VRIA	WFI UPDATED	OR COMPLETE	D BY			TITLE	# / Dan har /
11174M JEFFERSON	A, TNC	16							
3. SYSTEM NAME			DAY TELEPHO	NE		DA	ATE		
BEACH CLUB HOUSE CANAL ADDITIONAL ROUTING INFO	LANE		8. SUBMITTED						
			FOR	NEW 3	SYSTEM		CHANGE		REACTIVATE
MAILING ADDRESS			*OLD SYSTEM		ONLY IF CHANG				ELETE
151 E LEISURE LANE									
CITY	STATE ZIP CODI	E	SYSTEMS SE	EVING ANY F	RESIDENTS	PEOPLE LIVIN	IG IN A		
GRAPEVIEW	WA 98546	-9717			SYSTEM), COMP				
4. OWNER'S NAME (LAST, FIRST)	OWNER	NO.	9. NUMBER AC	TIVE RESIDENT	TAL	10. NUMBER		RESIDENTIA	ıL
OLYMPIC CANAL MAINTEN	ANCE 9	187							
ADDITIONAL ROUTING INFO				5	5 5 0			7	
ATTN BILLI MEIRNDORF MAILING ADDRESS									
310703 HWY 101					ION-RESIDE C.), COMPLETE				
CITY	STATE ZIP CODE	E			L CONNECTIONS				
BRINNON	WA 98:	320				27			
5. SYSTEM CONTACT PERSON	TITLE		12. ENTER AV	ERAGE DAIL	NON-RESIDEN	TIAL POPULATI	ON		*
DREW NOBLE - SMA 140			SERVED FO	DH EACH MONTE	H. MAKE ENTRY I	-OR EACH MOI	NIH.		
DAY TELEPHONE EVENIN	IG TELEPHONE		JAN.	APR.		JULY		Дост.	4.5
360-427-0654	360-427		FEB	4 MAY	sensing generality resonance of	AUG.		NOV.	
	OMINANT CHARACTERISTI CK ONE ONLY)	ic	MAR.	S JUNE	AT LEAST 25 OF	-1		DEC.	
Y PRIVATE: NON-PROFIT	RESIDENTIAL				WEEK FOR AT L				
1—/ <u>1</u>	ECREATIONAL			YES	X NO				
LOCAL GOVERNMENT	USINESS/INDUSTRIAL /	101			7.				
(COGNIT/CITT/POD/	ODGING / FOOD SERVICE	IAL		MBER OF SERVICE	CE	15. DISTRIBU		SERVOIR(S)
STATE	CHOOL / DAY CARE		CONNECTI	ONS METERED		TOTAL CA			
FEDERAL	THER (CHURCHES, ETC.)			1				5,000	GALLONS
						<u> </u>			
16. DOH	40.000005	10 1105 00		00 WELL 0	a couper	04 5011005	LOCATIO	N.	
SOURCE NAME NUMBER	18. SOURCE CATEGORY	19. USE 20	. 21. TREATMENT	22. WELL 2 DEPTH	3. SOURCE CAPACITY	24. SOURCE	LUCATIO	N.	_
	9 9								J O
LIST UTILITY'S NAME FOR SOURCE. IF SOURCE IS PURCHASED OR	WELL WELL FIELD SUBFACE SPRING FRANGY INF GAL. INTERTIE PUNCHASE-TREATED PURCHASE-TREATED	CY	z z						RNG.
INTERTIED, LIST SELLER'S ID# AND NAME USING FOLLOWING	E E INF.	AL NCY NCY	ATION ATION	(FEET)	(GPM)	1/4, 1/4 SEC.	SEC. NO.	TWP	RNG.
FORMAT: XXXXXX/NAME EXAMPLE: 77050Y/SEATTLE	WELL WELL FIEL SURFACE SPRING RANNEY / INTERTIE	PERMANENT SEASONAL EMERGENCY	NONE CHLORINAT FILTRATION FLUORIDAT OTHER			-			\$WTR E
	N N S & Z Z 2 2		88552			515 1.1	<u> </u>	OSN	
SO1 ACQ541 WELL 1 SO2 WELL #2	INACTIVE	X 08/11	11994	66		NE/SW	21	25N	02%
503 WELL #3	TNACTIVE	08/09							
S04 WELL #4	INACTIVE	08/09							
SOS WELL #5		X		63		NE/SW	21	25N	02W
S06 WF S01 & S05	X	X	X	63	12	NE/SW	21	15N	
							mer.	1	
25.	MINIMUM REQUIRE 26. JAN		MAR APR		E IUN JUL	AUG SI	EP O	CT ! NO	DV DEC
20.	25. 0	0	0 0		0 0	0	0		0 0
APPROVED SERVICES (PER PLANS)		V	7 1 0	1 4	V V	91	V	V)	21 1
SYSTEM IN CRITICAL WATER SUPPLY SERVICE AREA?	755 INO	GW MGM	T AREA?	YES	NO FOR LH	ED		1	
	ATURE OF DOH REVIEWER		vers and her		1 035 01	DAT	E	The state of the s	
							,	The state of the s	



Advertising Receipt

Leader

226 Adams Street Port Townsend, WA 98368 Phone: (360) 385-2900 Fax: (360) 385-3422

Washington State Dept of Ecology Water Resources PO Box 47775 Olympia, WA 98504-7775

Cust#:

01100442 000

Ad#:

04505393

Phone:

Date:

11/01/01

Ad taker:

ap

Salesperson:

Classification:

990

Description	Start	Stop	Ins.	Cost/Day	Surcharges	Total
01 Leader	11/07/01	11/14/01	2	45.12		90.25
Payment Reference:					Total:	90.25
Credit Card Number:					Tax:	0.00
Credit Card Expiration:					Net:	90.25
Credit Card Verification #:					Prepaid:	0.00
Credit Card Verification Amt:	0.00				Total Due	90.25
					Total Due	90.25

State of Washington
Department of Ecology
notice of application to appropriate public
water

TAKE NOTICE: That Olympic Canal Maintenance Corp of Brinnon, Washington February 27, 1998, under Application No. G2-29605 fled for a permit to appropriate public waters, subject to existing rights, from four wells in the amount of 40 gallons per minute as needed year round each year for multiple domestic supply. The source of the proposed appropriation is located within the NW 1/4 SE

THIS ITEM WAS PAID BY M/c 53000294 0890 0004

DAVE ANDRESEN 253-852-3687



STATE OF WASHINGTON DEPARTMENT OF ECOLOGY NOTICE OF APPLICATION TO APPROPRIATE PUBLIC WATER

TAKE NOTICE: That Olympic Canal Maintenance Corp of Brinnon, Washington February 27, 1998, under Application No. G2-29605 fled for a permit to appropriate public waters, subject to existing rights, from four wells in the amount of 40 gallons per minute as needed year round each year for multiple domestic supply. The source of the proposed appropriation is located within the NW 1/4 SE 1/4 Section 21, T. 25 N., R. 2 W. W.M., of Jefferson County, Washington. Protests of objections to approval of this application must include a detailed statement of the basis for objection; protests must be accompanied by a two dollar (\$2.00) recording fee and filed with the Department of Ecology, at the address shown below, within thirty (30) days from November 14,

Department of Ecology, SWRO PO Box 47775 Olympia, Washington 98504-7775 5393 11/14





STATE OF WASHINGTON DEPARTMENT OF ECOLOGY

P.O. Box 47775 • Olympia, Washington 98504-7775 • (360) 407-6300

October 25, 2001

Dave Andresen Beach Club House Canal Lane 20538 97th Avenue South Kent, WA 98031

Dear Mr. Andresen:

Re: Preliminary Permit to Drill and Test a Well Under Application No. G2-29605 for Olympic Canal Maintenance Corp.

The application requested the withdrawal of public ground water at a rate of 40 gallons per minute (gpm) for multiple domestic supply. The well site is located within the NW¼ SE¼, Section 21, T. 25 N., R. 2 W.W.M., of Jefferson County. Presently, it appears that your intent is drill a new well which would replace your existing wells. The conditions in this preliminary permit assume that scenario and thus describe testing for the new well. If use of some or all of your existing wells is anticipated in conjunction with your new well, please contact Ecology to see what multiple well testing might be required.

The Department of Ecology's goal is to prevent seawater intrusion rather than deal with it after the fact. The Water Quality Standards for Ground Waters of Washington State (Chapter 173-200 WAC) and other statutes grant Ecology authority to make water right decisions based upon seawater intrusion potential. Unless it can be proven that your proposed withdrawal will not lead to seawater intrusion, your water right application will be denied.

You are hereby granted a Preliminary Permit to proceed with drilling and testing of the well. It is important to note that you must comply with the conditions of this Preliminary Permit within the time period specified or else the application upon which it is based shall be automatically canceled. Please make sure that your consultant and/or driller receive(s) a copy of this Preliminary Permit to ensure compliance with all conditions. Also, please check with the Jefferson County Health Department to determine whether well site approval is required prior to well construction. This letter serves as a Preliminary Permit subject to existing rights and the following conditions:

- 1. This Preliminary Permit will remain in effect until November 1, 2002, unless sooner revoked by Ecology.
- All water wells constructed within the state shall meet the minimum standards for construction and maintenance as provided under chapter 18.104 RCW (Washington Water Well Construction Act of 1971) and chapter 173-160 WAC





(Minimum Standards for Construction and Maintenance of Water Wells).

- 3. In accordance with WAC 173-160-205 wells shall not be located within certain minimum distances of potential sources of contamination. In general, wells shall be located at least 100 feet from a sewer, septic tank, privy, or other source of contamination. Wells shall not be located within 1,000 feet of a solid waste landfill. Minimum distances shall also comply with state and local health regulations.
- 4. An access port shall be installed and maintained. In order to facilitate accurate recovery data collection, the system shall incorporate backflow check-valve(s) that will prevent water from flowing back into the well when the pump is shut off.
- 5. The well shall be tested at a **constant rate** no less than the maximum design rate at which the well source will be used. The Washington State Department of Health (DOH) Water System Design Manual (DOH #331-123, June 99), Appendix E provides guidelines for designing and conducting the aquifer test (available at www.doh.wa.gov/ehp/dw). For water table aquifers, pumped water produced during the test shall be routed away from all wells and discharged such that this water will not recharge the drawdown cone during the test.

Pumping during the test shall be conducted for a **minimum** of 24 hours, with stabilization of the pumping well water level occurring for at least the last four of those hours. Stabilization is defined as a drop in water level of less than or equal to 0.1 foot drawdown per hour during pumping. Depth to water shall be measured in feet, using 10ths and 100ths of a foot rather than inches.

At the completion of pumping, recovery data shall be collected from the well until the pumped well nears pre-pumping static conditions and the water level recovery rate is less than 0.1 foot per hour.

6. The following water quality sampling and analyses will be used by Ecology when evaluating your application. Please be aware that the state or county health department may require additional testing prior to the approval of your project. If your project involves a public water system, please check with the appropriate health agency to determine what additional testing is required prior to conducting the test. All water sample analyses conducted pursuant to this Preliminary Permit shall be performed by a laboratory accredited by the Washington State Department of Ecology.

Ground water sampling and analysis shall occur as follows:

• In order to evaluate the potential for seawater intrusion, (3) ground water



samples from the pumped well shall be analyzed for chloride and conductivity. These samples shall be collected at the following intervals:

- one (1) sample during the initial 30 to 60 minutes of pumping,
- one (1) sample approximately mid-way through pumping, and
- one (1) sample within the last 15 minutes of pumping.
- Please check with the State Department of Health for their additional sampling and analysis requirements.
- 7. When aquifer testing is completed, the data shall be compiled into a report. This report shall be submitted to the Ecology, Southwest Regional Office and shall include the following:
 - a. A well construction report (well log) for the pumping well which includes the total depth, the screened interval depth(s), and the pump intake depth.
 - b. Land surface elevation for the pumping well and method used for determining.
 - c. A legible table including the pumping rate and all water measurement data collected during pumping and recovery.
 - d. A copy of all laboratory test results.
- 8. In addition to the above, a complete water well report for the well shall be submitted by the driller to Ecology within thirty (30) days of completion.
- 9. These test results are needed in order to properly analyze the effects of the proposed pumping. Failure to follow correct methodology such as that outlined in the DOH guidelines, may be reason to require that the aquifer testing be repeated.
- 10. All expenses, risks, and liabilities incurred during well testing shall be borne by the applicant. If senior water right holders are adversely affected during any portion of the aquifer test, the test shall be terminated immediately.
- 11. This Preliminary Permit grants the right to use this well for testing purposes only. No further use will be allowed from the well except as authorized under the accompanying TEMPORARY PERMIT. Approval will not be considered until the above conditions have been met.
- 12. The granting of this Preliminary Permit shall not be construed, by inference or



October 25, 2001 Page 4

otherwise, that subject application will ultimately be approved. If the applicant fails to comply with the terms of this Preliminary Permit, it and the application upon which it is based, will be automatically canceled.

Any person seeking to appeal this action must submit a written request, within 30 days of receipt of this order, to the Washington Pollution Control Hearings Board (4224 6th Avenue SE, Building 2, P.O. Box 40903, Olympia, WA 98504-0903). At the same time, send a copy of the appeal to the Director of the Department of Ecology (P.O. Box 47600, Olympia, WA 98504-7600). These procedures are consistent with those of the Environmental Hearings Office, Pollution Control Hearing Board (Chapter 43.21B RCW and its implementing regulations).

Should you have any questions regarding this Preliminary Permit please contact Marie Peter at (360) 407-0279. For questions regarding testing procedures or requirements, please contact Tom Culhane at (360) 407-0297.

Sincerely,

J. Mike Harris
Section Supervisor
Water Resources

JMH:MP:th

Cc: Jerrod Davis

Olympic Canal Maintenance Tracts office

File #G2-29605





STATE OF WASHINGTON DEPARTMENT OF ECOLOGY

P.O. Box 47775 • Olympia, Washington 98504-7775 • (360) 407-6300

October 25, 2001

Dave Andresen Beach Club House Canal Lane 20538 97th Avenue South Kent, WA 98031

Dear Mr. Andresen:

Re: Permit for Temporary Use of Water in Conjunction with Water Right Application No. G2-29605 for Olympic Canal Maintenance Corp.


On February 27, 1998, Olympic Canal Maintenance Corp. applied for a permit to appropriate public ground water in the amount of 40 gallons per minute. Olympic Canal Maintenance Corp. currently serves three full-time and 42 recreational connections within Olympic Canal Tracts Addition No. 1. Although the system has two wells, the combined yield of these wells is only 3-4 gallons per minute. The State Department of Health has determined that the source capacity is inadequate for this system and has "red-tagged" the system.

Olympic Canal Maintenance Corp. has authorization to construct and test an additional well within the NW ¼ of the SE ¼ of Section 21, T. 25 N., R. 2 W.W.M. under a preliminary permit issued by Ecology. Because inadequate source capacity poses a threat to public health for existing residents, Ecology is authorizing the temporary use of ground water from the new well. This letter serves as temporary authorization for the use of the well, and is subject to the following conditions:

- 1. The effective date of this temporary permit is October 25, 2001.
- 2. The instantaneous withdrawal rate shall not exceed 40 gallons per minute.
- 3. Use of water under this temporary permit shall be limited to serving existing connections within Olympic Canal Tracts Addition 1.
- 4. The maximum amount of water withdrawn under this permit shall not exceed an average of 5,000 gallons per day, or 5.6 acre-feet per year.
- 5. The water appropriated under this application will be used for public water supply. The State Board of Health rules require public water supply owners to obtain written approval from the Office of Water Supply, Department of Health, 1112 SE Quince Street, PO Box 47890, Olympia, Washington 98504-7890, prior to any new construction or alterations of a public water supply system.







- 7. Installation and maintenance of an access port as described in Chapter 173-160 is required. An air line and gauge may be installed in addition to the access port.
- 8. Withdrawals authorized under this permit may be subject to regulation, if necessary, to protect existing rights.
- 9. This temporary permit expires on October 24, 2004, or upon issuance of a formal water right permit under Application No. G2-29605. This authorization may be extended if a written request justifying an extension is made at least 30 days prior to expiration.

This permit is subject to revocation if Olympic Canal Maintenance Corp. fails to comply with any of the conditions specified above. In issuing this temporary permit, the Department of Ecology in no way guarantees that a formal permit will be granted to withdraw water from this well.

This order may be appealed. Your appeal must be filed with the Pollution Control Hearings Board, PO Box 40903, Olympia, WA 98504-0903 within thirty (30) days of the date this Order was mailed by the Department of Ecology. At the same time a copy of your appeal must be sent to the Department of Ecology, c/o Appeal Coordinator, PO Box 47600, Olympia, WA 98504-7600. Your appeal alone will not stay the effectiveness of this order. Stay requests must be submitted in accordance with RCW 43.21B.320. These procedures are consistent with Chapter 43.21B RCW.

If you have any questions concerning this authorization, please call Marie Peter at (360) 407-0279.

Sincerely,

J. Mike Harris

Water Resources Supervisor

JMH:MP:th

Cc: Jerrod Davis, Department of Health

Olympic Canal Maintenance Corp office

File No. G2-29605







STATE OF WASHINGTON

DEPARTMENT OF ECOLOGY

P.O. Box 47775 • Olympia, Washington 98504-7775 • (360) 407-6300

October 25, 2001

Dave Andresen
Beach Club House Canal Lane
20538 97th Avenue S
Kent WA 98031

Dear Mr. Andresen:

Re: Water Right Application No. G2-29605

We have received your application for appropriation of water and it has been assigned the number referenced above. If you contact us in the future regarding this application, it will help us serve you more quickly if you refer to this application number.

Please complete the following two steps:

1. Enclosed is a notice of your application, which must be published <u>once a week for two consecutive weeks</u> in a newspaper published in **Jefferson** County. The newspaper should have general circulation in the locality where the water is to be diverted and used, and must be qualified as a legal newspaper. Publishing the notice in a remote part of the county, when not necessary, may be cause for you to be required to republish the notice in a designated newspaper. The enclosed newspaper list may help you select an appropriate newspaper for the area.

Publication should start within 30 days from the date of this letter.

or Carrael

To assure accuracy, it is your responsibility to check the notice carefully before having it published. If you find an error, please contact this office for correction and/or resolution. If we later find an error in your public notice, you will be required to re-publish an amended notice at your expense.

2. After publication, the publishing newspaper should provide you with a notarized original Affidavit of Publication, which should be forwarded to our office as soon as possible. Please do not send a photocopy of the affidavit.

Community water systems are required to be approved by either the local health department or the Department of Health depending upon system size. If you have not already done so, we suggest that you contact either your local health department or the Department of Health, Southwest Drinking Water Operations, Thurston Airdustrial Center, Bldg 3, PO Box 47822, Olympia, Washington 98504-7822 for further information.

If you have any questions or concerns about any of this information, please call (360) 407-0240. Thank you for your attention to this matter.

Sincerely,

Sheri Carroll

Water Resources Program

SC:th (affidavit of publication.doc)







STATE OF WASHINGTON

DEPARTMENT OF ECOLOGY

NOTICE OF APPLICATION TO APPROPRIATE PUBLIC WATERS TAKE NOTICE:

That Olympic Canal Maintenance Corp of Brinnon, Washington on February 27, 1998, under Application No. G2-29605 filed for a permit to appropriate public waters, subject to existing rights, from four wells in the amount of 40 gallons per minute as needed year round each year for multiple domestic supply. The source of the proposed appropriation is located within the NW¼ SE¼ Section 21, T. 25 N., R. 2 W.W.M., of Jefferson County, Washington.

Protests of objections to approval of this application must include a detailed statement of the basis for objections; protests must be accompanied by a two dollar (\$2.00) recording fee and filed with the Department of Ecology, at the address shown below, within thirty (30) days from:

(Last date of publication to be entered above by publisher)

NOTICE MUST BE PUBLISHED ONCE A WEEK FOR TWO CONSECUTIVE WEEKS

Department of Ecology, SWRO PO Box 47775 Olympia, Washington 98504-7775

ECY 040-1-1 Rev 2/79

Notice









STATE OF WASHINGTON

DEPARTMENT OF HEALTH

SOUTHWEST DRINKING WATER OPERATIONS

2411 Pacific Ave. • P.O. Box 47823 • Olympia, Washington 98504-7823 (360) 664-0768 • FAX (360) 664-8058

TDD Relay 1-800-833-6388

October 4, 2001

Dave Andresen
Beach Club House Canal Lane
20538 97th Avenue South
Kent, Washington 98031

Dear Mr. Andresen,

Subject:

Beach Club House Canal Lane (aka Olympic Canal Tracts) Water System, ID #11196M, Jefferson County; Existing System Approval and New Source Approval Process, Group A Transient Non-Community (TNC) Water System

I would like to thank you, the Beach Club House Board Members, and Jim Parker of Jefferson County Public Utility District (PUD) for meeting with me on August 30, 2001 to discuss the status of the Beach Club House Canal Lane (BCHCL) water system and the steps required to bring your water system into substantial compliance.

As you know, your water system has been placed in an inadequate status (RED Operating Permit) due to several reasons. Jefferson County Environmental Health Department (EHD) found deficiencies during a routine Sanitary Survey conducted on November 20, 1999. A Bilateral Compliance Agreement (BCA) was then issued on February 9, 2000, outlining corrections needed to be made to the water system. The BCA required that a sanitary control area be documented, wellhead improvements be made, a coliform monitoring plan be generated, water quality sampling be conducted, and a disinfection system be installed. As of this date, DOH has received documentation from Jim Parker of Jefferson PUD for all of the items contained in the BCA. However, remaining issues of concern to the Department of Health (DOH) are inadequate source capacity and the lack of water rights.

Jefferson PUD's analysis of the system indicated that both of the existing wells are experiencing decreased source capacity (i.e., from a capacity of 12 gallons per minute [gpm] to less than 7 gpm). Even with the existing storage capacity, peak demands are most likely not being met to

Dave Andresen Page 2 October 4, 2001



90

serve the existing five (5) residential and twenty-seven (27) non-residential connections. Based on this information, additional source capacity is required.

One way to increase source capacity is to drill a new well. However, without any water rights, the only way to drill a new well is to drill an EXEMPT well. The water usage from an EXEMPT well cannot exceed more than 5,000 gallons per day (gpd). Based on water usage records from your water system, it appears that the water usage is less than 5,000 gpd. It is my understanding that you applied for water rights to the State Department of Ecology (DOE). If you choose to drill an EXEMPT well, particularly if the new well is deeper than the existing wells, you must consult with DOE as soon as possible regarding your existing water right permit application. Drilling an EXEMPT well that is deeper than your existing wells may change the status of your existing permit application. In addition, drilling an EXEMPT well would require that you record water usage readings as frequently as possible (daily readings if possible) to verify that water usage is less than 5,000 gpd.

Once the BCHCL water system improves the source capacity, DOH can change the Operating Permit from RED to GREEN AT CAPACITY. At Capacity means that your water system will be placed in an adequate status to serve the existing five (5) residential and twenty-seven (27) non-residential connections. Converting non-residential connections to residential connections will not be permitted until adequate water rights are obtained.

I look forward to working with you to bring your water system into substantial compliance. Please do not hesitate to call me regarding this letter or your water system at (360) 586-2510.

Sincerely.

JERROD L. DAVIS, P.E. WSDOH Regional Engineer

cc: Russ Austin, Manager, Beach Club House Canal Lane Larry Fay, Jefferson County Environmental Health

Jim Parker, Jefferson County PUD

Marie Peter, WSDOE



STATE OF WASHINGTON DEPARTMENT OF ECOLOGY

P.O. Box 47775. Olympia, Washington 98504-7775 (360) 407-6300

April 3, 1998

Dear Water Right Applicant:

Re: Water Application No. G2-29605

We have received your application for a water right and have assigned the application number indicated above. It would help us if you referred to it by number in future correspondence.

Due to a shortage of staff to meet the demand for service, new applications are being accepted and filed for future processing, but a public notice will not be sent at this time. Because we have approximately 5,000 pending applications for water rights statewide, it may be some time before we can get to your application. When we begin processing your application, we'll prepare a public notice and send it to you with publication instructions. It is very important that you notify us of any change of address or ownership of the property; or, if your plans for water use change.

We are working on the oldest applications on file as quickly as we are able. We are also looking for ways to speed up decision making. Please keep in mind that filing an application for water use does not authorize use of the water. With the many complexities of water law, including issues such as senior rights, fish habitat, and instream flows, favorable permit decisions are not always possible. I regret that a decision on your application cannot be made sooner and strongly advise against investing further in your project unless you are issued a water right permit.

I apologize that this is the best we can do currently. To better manage limited staff time, we have set the following office hours:

Telephone Calls Walk-ins

Mondays and Wednesdays Tuesdays and Thursdays

8:00 am to 4:00 pm 8:00 am to 12:00 (noon)

We will respond to your questions and concerns as soon as possible. Thank you for your continued patience.

Sincerely,

Water Resources Supervisor

JMH:th (ackapp.doc)

